



### Sensor and Optional Camera:

Motion sensor, ambient light sensor and optional HD IP camera.

### RFID Inside:

Optional RFID reader Mounted internally for a sleek design.

### 7" Touchscreen, Full Color Display:

- Navigate with touchscreen or keys
- Adjustable back-lighting
- LED screen is easy to read in direct sun
- Customizable text and images

### Intuitive Navigation:

Navigating any function is simple with user prompts, including tonal cues and flashing keys to guide users through steps.

### Reliable Performance:

New CPU and software improves system performance and communication across multiple networked devices.

### Effortless User Experience:

User-focused system is clear, logical, and minimizes steps for visitors.

### Upgradeable:

Out of the box ready for 36 doors – Upgrade at any time for up to 64 doors with a purchased license key.

### All-Weather Reliability:

New housing with added sealants for better performance in harsh environments.

## LINEAR EntryPRO SERIES

**EP-736** | Upgradeable 36-Door Telephone Entry

## Next Generation Panel

Linear® EntryPro EP-736 is perfect for mid-sized and larger residential and commercial applications. The EP-736 features a large, full-color 7" touch screen and intuitive user experience that is easy to navigate and customizable. The EntryPro series features improvements across hardware and software for improved system performance, communication and all-weather reliability.

- New generation panel looks the same on the outside but is packed with upgraded hardware and software on the inside.
- New software improves network communications.
- Redesigned housing features an improved weatherproofing seal.
- Full-color 7" touch screen.
- Improved 2-way audio voice calls.

EntryPro EP-736 is fully browser-managed, and is out of the box ready for 36 doors. It is easily upgradeable to 64 doors and requires no additional software, so it won't become obsolete as technology changes. It is compatible with a wide range of entry credentials, new and old, allowing administrators to transition to new technology at their own pace.

PRODUCT DIMENSIONS		EVENT ACTION		
Product Size	EP-736: 16.3"(L) x 13.1"(W) x 4.6"(D) EP-EXN: 14.2"(L) x 13.3"(W) x 3.6"(D)	Event Action Input	Reader Event, Physical Input, Door Position, REX, System Event, API	
Product Weight	EP-736: 15.0 lbs. EP-EXN: 7.2 lbs.	Event Action Output	Outputs, Dashboard, eMail, SMS, Back up SD / FTP, Threat level, Video tag	
Recessed Mounting 1" Trim Ring (PN 720-100123)	Hole Size: 16.5"(L) x 13.25"(W) x 3.5"(D) Outside Dimensions: 18.6"(L) x 15.35"(D)	Power (per board)	12VDC from provided DC plug-in power supply - Power for two modules & readers	
Recessed Mounting 2" Trim Ring (PN 720-100124)	Hole Size: 16.5"(L) x 13.25"(W) x 3.5"(D) Outside Dimensions: 21.35"(L) x 17.6"(W)	Total System Access Levels	250	
ITEM	EP-736	Users per system	10 000	
Warranty	2 Years Hardware and Software	Access cards	120,000	
UL294 Series 6	UL294 Series 6, Attack class 2, FCC	Cards per person	32	
Available Modules	2-Door Module, 2 Door Expansion, 2 Door Add on to Expansion	Binary Card Decoder	Yes - 26 - 128 bit with or without facility code, Facility Code Only	
System Integrity	128 bit Encryption (User database and events) / SSL / HTTPS / PHP	User-defined data fields	20 user fields, Flat File Import Option	
Language	English	Database Import Tool	Yes, CSV	
System Control	Web Browser compatible	Day Light Savings Time "DST"	Automatic, Editable dates if future requirement	
Pre Configured Doors Per System	2 on board, expandable to 36 or 64 doors	SMTP	On / Off Manual, PC Sync	
Max Readers per system	Expandable up to 128 in/out	Client Time Zone Configuration	Yes, Each module is selectable	
Max Client/Expansion Modules Per Site	32	Time specifications (schedules)	250	
Distributed Processing	Every module contains database and events	Time spec groups (Schedule groups)	64	
Outputs Per Board	4 Form C SPDT / Dry 5 Amp	Holidays, Holiday Groups	60, 4 groups	
Outputs Times	Hours, Min, Sec., by set time and/or repeat quantity.	Online event history log	50,000 transactions	
Notification	Yes, email and SMS event notification	Transaction Types	Action of any type, Administrator Change Logging "Audit", and System Diagnostic Events.	
Inputs per board	8- 6 Analog Selectable for type, 2 Pre-assigned (Tamper, Postal)	Archive for transactions	Manual, Automatic daily, Automatic by 90% full	
Input types	NO / NC Parallel Resistor, NO / NC Series Resistor, NO / NC Unsupervised	Archive for system configuration files	Manual, Automatic daily	
Predefined Door Configuration	Lock, Prop (Output) REX, Door Position (Input)	Report Utility	Internal Smart Report Utility	
Environmental Temperature	-22°F to 149°F (-30°C to 65°C) Humidity: 5% to 95% non-condensing	Administration / User Roles	Super for Entire System, Admin designated by doors (building), Customizable by Users	
Power Requirements	9VDC – 15VDC, Includes 12VDC Plug in Power Supply	Maximum concurrent web users	25	
Remote Management Console	Optional	Maximum defined administrative users	160	
USER INTERFACE FEATURES		ORDERING INFORMATION	Part #	Model #
System Fully Web Controllable	Yes	EntryPro 736	720-200736	EP-736
Action Icons	Door Unlock, Toggle, Aux outputs	EXN Door expansion unit	720-100104	EN-EXN
Alarm Acknowledgement	Yes	ACM 2-Door Module	720-200105	EP-ACM
Logo Placement	Yes - Ability to place Dealer or End user logo into system	License Upgrade: 36-64 Door	720-100226-VL	EN3664UP

