

### No-Cut Door Strike

**SD-995C-D3Q** 12/24VDC, UL

The **SECO-LARM®** No Cut Door Strike can be used to convert cylindrical lock sets into an electronic access-controlled locking system. Combine with an optional **SECO-LARM®** digital keypad for keyless high security.

#### Features:

- Low profile: Strike is only 1 1/16" deep for use with aluminum frames
- Field-selectable for fail-safe or fail-secure operation
- Mounting tabs included for mounting to hollow aluminum & metal doors
- Reversible non-handed design fits either right-hand or left-hand doors
- For indoor use only
- Static strength – 1,500 lbs. (6673N)
- Dynamic strength – 70ft-lbs. (95J)
- 12/24 VDC Operating voltage
- Tested to 100,000 cycles (UL Tested), tested to 1,000,000 cycles (Factory Tested)
- Low current draw: 300mA@12VDC, 150mA@24VDC
- No horizontal or vertical adjustment



#### Specifications:

Model	SD-995C-D3Q	
Operating voltage	12/24 VDC	
Current draw	12VDC	300mA
	24VDC	150mA
Latch throw	9/16" (15mm)	
Keeper width	1 7/16" (36mm)	
Static strength	1,500 lbs (6673N)	
Dynamic strength	70ft-lbs (95J)	
Endurance	100,000 cycles (UL Tested), 1,000,000 cycles (Factory Tested)	
Operating temperature	32°~120° F (0°~49° C)	
Operating humidity	0~85%	
Dimensions	4 7/8" x 1 1/4" x 1 1/16" (124x32x27.5 mm)	

#### Also Available from SECO-LARM®:



**SD-995C**  
**SD-995C24**  
Electric Door Strike  
for Metal Doors



**SD-991A-D1Q**  
Mini No-Cut  
Electric Door Strike

#### SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2018 SECO-LARM U.S.A., Inc. All rights reserved.

All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

**SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®**

PI\_SD-995C-D3Q\_180621.docx