



Wave-to-Open Sensor

SD-927PKC-NEQ English*, No-Touch SD-927PKC-NEVQ English*, No-Touch, Override Button Conforms to UL294

The ENFORCER Wave-to-Open Sensor uses IR technology to allow egress from a protected area or activate a device with just a wave of a hand. Since no touch is required, this sensor is suitable for use in hospitals, clinics, labs, clean rooms (to reduce the risk of contamination), schools, factories, or offices. The SD-927PKC-NEVQ adds a manual override button.

Features:

- Operating voltage, 12~24 VAC/VDC
- Range adjustable from 23/8"~8" (6~20 cm)
- Stainless steel single-gang faceplate
- 3A relay, adjustable from 0.5~30 sec, toggle, or as long as hand is near the sensor
- Quick connect screwless terminal block
- LED illuminated sensor area for easy identification
- Selectable LED colors (turns from red to green or green to red when activated)

SD-927PKC-NEVQ

Adds manual override button as a backup to the sensor

Specifications:

Model		SD-927PKC-NEQ	SD-927PKC-NEVQ	
Operating voltage		12~24 VAC/VDC		
Current draw (max.)		120mA@12VDC		
Relay type		Form C dry contact NO/NC/COM, 3A@24VDC		
Override button	Switching capacity	N/A	3A@24VDC	
	Mechanical life	N/A	500,000 Cycles	
Response time		10ms		
LEDS	Standby	Red⁺		
	Triggered	Green [†]		
Output time		Adjustable, 0.5~30sec., toggle, or as long as		
		sensor is triggered		
Sensing range		Adjustable, 2 ³ / ₈ "~8" (6-20 cm)		
Operating temperature		-4°~131° F (-20°~55° C)		
Dimensions		2 ³ / ₄ "x4 ¹ / ₂ "x1 ¹ / ₈ " (70x114x28 mm)		
Weight		3-oz (85g)	3.9-oz (110g)	







SD-927PKC-NEVQ










Dimensions:

SD-927PKC-NEVQ shown




*French (SD-927PKC-NFQ, SD-927PKC-NFVQ) and Spanish (SD-927PKC-NSQ, SD-927PKC-NSVQ) faceplates also available.

†Reversible by jumper

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com





Ordering Information:

Wave-to-Open Sensors					
Model	SD-927PKC-NEQ	SD-927PKC-NFQ	SD-927PKC-NSQ	SD-927PWCQ*	
Language	English	French	Spanish	English, French, and Spanish Decals	
Photo	WAVE TO OPEN	OUVRIR SANS CONTACT	ABRIR SIN CONTACTO	© ENFORCER*	

Wave-to-Open Sensors with Override Button					
Model	SD-927PKC-NEVQ	SD-927PKC-NFVQ	SD-927PKC-NSVQ Spanish		
Language	English	French			
Photo	WAVE TO OPEN ENGINEERS ((((*/>)))) Manual Ovenide	OUVRIR DENFORCERS SANS CONTACT ((1 (1))) Commando Manuelle	ABRIR SIN CONTACTO DE ENFORCESE SIN CONTACTO DE ENFORCESE		

Sensor Only					
Model	CS-PD535-TAQ	CS-PD535-TBQ [†]			
Photo			For our full line of OEM/private label infrared sensors, contact SECO-LARM		
Description	1 ¹ / ₄ " (32mm) Sensor	1 ¹ / ₄ " (32mm) Sensor			

*For SD-927PWCQ specifications, visit www.seco-larm.com

[†]Special order. Contact SECO-LARM for details

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com

