WIRELESS COMMERCIAL KEYPADS.

The most reliable wireless keypads for any residential or commercial application.

SUPERIOR PERFORMANCE

Security+ 2.0® Technology Virtually Eliminates Interference, Improving Range

UNIVERSAL CONTROL

KPW250 Programs to All LiftMaster® Gate and Door Operators

MANUAL GATE OPERATION

With Constant Pressure Override* and Party Mode**



KPW250/KPW5 COMPATIBILITY CHART





KPW250					KPW5
Code/Radio Frequencies	Security+ 2.0 (Tri-Band 310/315/390 MHz)	Security+® (315 MHz)	Security+ (390 MHz)	Multi-Code® (300 MHz)	Security+ 2.0 (Tri-Band 310/315/390 MHz)
LiftMaster Gate Operators	2018 UL® 325 Compliant Gate Operators 2016 UL 325 Compliant Gate Operators with On-Board Receiver Security+ 2.0 Gate Operators with 850LM Receiver Installed	Security+ Gate Operators with On-Board Receiver Security+ Gate Operators with 312HM Receiver Installed	Security+ Gate Operators with LiftMaster 412HM Receiver Installed	-	2018 UL 325 Compliant Gate Operators 2016 UL 325 Compliant Gate Operators with On-Board Receiver Security+ 2.0 Gate Operators with 850LM Receiver Installed
LiftMaster Commercial Door Operators	Logic 5.0	Logic 4.0 and 3.0	Any Commercial Door Operator with 412HM Receiver Installed	-	Logic 5.0
Multi-Code® Receivers	-	-	-	109020, 109920, 109950, 302850,† 302101	-
LiftMaster Commercial Receivers	STAR1000, 850LM, 860LM	312HM	412HM	-	STAR1000, 850LM, 860LM

*Only available when paired with LiftMaster UL® 325 Listed Gate Operators with burgundy control boards.

**Party mode (gate hold open) feature on all LiftMaster Gate Operators with new firmware 4.2.

†302850—jumper must be set to Multi-Code 300 MHz.

© 2018 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc. 300 Windsor Drive, Oak Brook, IL 60523

LiftMaster.com

Multi-Code is a registered trademark of Nortek Security & Control LLC.
UL and the UL logo are trademarks of UL LLC © 2018 All Rights Reserved.
LMACCTOKPW 9/18

