

SterlingCool

CUTTING FLUIDS DIRECT

SterlingCool-18

SterlingCool-18 is a heavy duty soluble oil coolant that can be used on steel, stainless steel, carbon steel, alloy steel, exotic alloys, cast iron, ductile iron, aluminum, copper, titanium and most other ferrous and non-ferrous metals. Its triple action lubricating formula provides excellent tool life for the toughest applications while also keeping machines running clean and free of bad odors associated with bacteria. SterlingCool-18 is built tough and will provide long sump life. Excellent for tough machining applications including deep hole drilling and difficult form tapping operations.

LAB DATA

| | |
|----------------------|---------------------|
| Physical State | Yellow/Amber Liquid |
| Odor | Mild |
| Solubility in Water | Soluble in Water |
| PH 5% mix | 9.2 |
| PH Concentration | 9.8 |
| Residue | Liquid Film |
| Refractometer Factor | 1.0 |

Advantages

- No sump stench, no bad odors
- Triple Action lubrication formula
- DCHA free
- Excellent Lubricity
- Extremely clean
- Low foam formula



SterlingCool 18 does not contain nitrites, sulfur, chlorinated EPs, phenolic biocides or DCHA. Not for use on Magnesium.
To order or for more information, please find us at cuttingfluidsdirect.com