



MOTORCYCLE PRODUCTS-DESIGN & MANUFACTURE

www.hoppeindustries.com

22667 FM 15 Troup, TX 75789

Ph.(262) 552-2770

Fax (262) 552-2778

HPBY-0880 & HPBY-0881

Installation Instructions for Yamaha Royal Star Tour Deluxe Fairing w/4 Speakers

Your new fairing has been shipped with all the necessary hardware for a basic installation to the Yamaha windshield mounts. If you have any questions after reading the information in this sheet, please contact Hoppe at: help@hoppeindustries.com or call us. **Please read all the way through the instructions before starting the installation**, as five minutes spent now may save you many times that later. Install the fairing to check for fitment BEFORE painting it,

Before you start:

Please note that some inside areas of the fairing front are visible when the fairing is assembled. It is important that you let your painter know to paint the inner edge for at least 1" when they paint the front so that no primer is left showing.

Important safety note-please read!!!

Any modification like adding a fairing, extended controls, different handlebars, etc., **will have an effect on your bike's handling.** That doesn't mean bad, just different. Take some time to get to know your bike after installing your fairing. The decreased wind felt by the use of a fairing can affect your perception of speed, leading you to possibly drive faster than you are aware of. Crosswinds and passing large vehicles will have an effect because of the larger front surface area. Handling in parking lots may feel slower. Last, but definitely not least - take the time BEFORE your first ride to become familiar with your new radio's controls. Set the preset channel buttons, adjust the volume and tone, know how to turn it off & on without having to take your eyes off the road. Your new fairing will give you miles of smiles and get you there less fatigued-but not if you plow into something while playing with the radio!!!!

NOTE:

The following instruction sheet shows a detailed installation. If you do not wish to remove the tank and trim items the power cable can be run under the tank. You can just thread it along the right side of the frame, from next to the neck cover, over the forward motor mount, and out the rear of the tank to merge with the hoses and cables between the upper frame rails. !

Note: Stereo includes a CD Player. The player may skip due to the vibration of your bike.

Materials supplied:

- (2) Stainless Bushing sets (four pieces)
- (2) Chromed 8mm Flat Washers
- (4) Stainless Steel Flat Washers
- (4) M8 x 20mm long Socket head Capscrews
- (1) Power Cord & Connectors
- (1) #242 Loctite