

.

VAPNING: I lea of this aguinma

.

CALITION: The device shall only be used if the battery cover

DSP algorithm: Digital Signal Proc

● INTRODUCTION ●

Installation Setup and Operation

 $d = [\frac{3.5}{V_1}]\sqrt{P} \qquad d = [\frac{3.5}{E_1}]\sqrt{P} \qquad d = [\frac{7}{E_1}]\sqrt{P}$ $/ \qquad 0.12 \qquad 0.23$ $/ \qquad 0.38 \qquad 0.73$

→ ABOUTUS →

Dr Trust

Dulco Ovimeter 216

the recommended separation distance on interesting the activated using the equation applicable to the frequency of the transmitter, where P is the maximum output power rating of the transmitter in wats (W) according to the transmitter manufactur NOTE 1.4 80 MHz and 800 MHz, the separation distance for the higher frequency range applies.

NOTE 2 These guidelines may not apply in all situations.
Electromagnetic propagation is affected by absorption and reflection structures, objects and people. Dr Trust[®] 20 Dr Trust[®] 21

Contact us India: +91-7527013265 /+91-9356658436 Website: www.drtrust.in Corp Website: www.nureca.com Email: customercare@nureca.com Connect with us on social networks Facebook: @drtrust Instagram: @drtrustisin Youtube: Nurecal Isa

Dr Trust° 22

● INDEX ●

OPYRIGHT®2021 NURECA LTD ALL RIGHTS RESERVED

Dr Trust 🖪 Scan to View Product Demo Video www.drtrustusa.com/216

SAFETY •

Dr Trust° 23