



DUAL PURPOSE DIAGNOSTIC LEAK LOCATOR™

P/N # 95-0130

Made for ease-of use, this new all-in-one unit is engineered to quickly test the integrity of EVAP systems, intakes, turbo, boosted, low and high pressure systems, all without dyes or contaminants so it's safe for the vehicle, safe for the technician and safe for the environment. Variable pressure, variable flow replicate the full load of a running vehicle and allow the technician to adjust flow as needed to find minuscule faults in every type of vehicle, even heavy duty trucks. This technology dramatically increases shop efficiency by giving the ability to switch from low pressure to high pressure, with the flip of a switch.



DUAL LEAK LOCATOR™

- Variable Pressure | Variable Flow
- 40X Typical EVAP Pressure
- Compact, Rugged Design
- Professional Grade Strong
- Made with Steel and Billet Aluminum
- Runs on Compressed Air
- Powered by 110-250 VAC or 12 VDC
- Free of Dyes & Contaminants
- 2-20+ PSI Range / 0-2+ PSI Range
- Performs Decay / Leak Down Tests
- Weighs only 27 lbs.

TURBO Vapor Quickly Locates:

- Turbo / Boost Leaks
- Charge Air Cooler Leaks
- Exhaust System Leaks
- Wind and Water Leaks
- Cabin Leaks
- Intake System Leaks
- Seals, Gaskets, Hoses, Fittings Etc.

EVAP Quickly Locates:

- Vacuum
- EVAP (Fuel Vapor Recovery)
- Exhaust
- Oil
- Manifolds
- Brake Boosters
- EGR Valves
- Seals, Gaskets, Brake Vacuum Hoses
- Cooling Systems
- Wind and Water Leaks
- Diaphragms
- Central Locking Systems
- And Much More



www.RedlineDetection.com
+1.714.451.1411



**Save Time.
Make More Money.**

- Reduce Diagnostic Time
- Increase Fuel Economy
- Eliminate Guess Work
- Sell More Parts
- Eliminate Comebacks

DUAL PURPOSE DIAGNOSTIC LEAK LOCATOR™

Low Pressure for EVAP
High Pressure for TURBO/DIESEL/HD



KIT INCLUDES:

Includes: Accessory Storage Case, 1.9" Power Intake™, 1.9" Power Intake™, Halogen Inspection Light, AC Power Cable, Vapor Producing Fluid, Hex Key, Block Off Coupler, O2, Temperature, and Pressure Sensor Port Adaptors, EVAP Service Tool Kit, Cap Plug Kit, Standard Cone Adaptor.

Dimensions	13.5 in x 9 in x 15 in (34.29 cm x 23 cm x 38 cm)
Weight	27 lbs (12.25 kg)
Power Supply	110-230V AC or 12V DC
Pressure Supply	Compressed Air
Output Pressure (EVAP)	0 to 2+ PSI (0 to 0.14+ BAR)
Output Pressure (TURBO)	2 to 20+ PSI (0.14 to 1.4+ BAR)
Operating Temperature	0°F to 140°F (-17°C to 60°C)
Operating Humidity	No Restrictions
Operating Altitude	No Restrictions
Operating Modes	Smoke Cycle / Air Only Cycle
Housing Material	Steel
Smoke Chamber Material	Billet Aluminum
Smoke Chamber Assembly	Bolted
Smoke Chamber Warranty	Lifetime
Dual Leak Locator™ Warranty	1 Year

REDLINE
DETECTION.COM

www.RedlineDetection.com

+1.714.451.1411

MADE IN

CALIFORNIA
USA

P/N # 95-0130