



The AUTOPA Square RetractaPost 745

The Square RetractaPost is a simple, cost effective, yet highly effective way to prevent unwanted vehicle access. The Square RetractaPost is raised and lowered vertically. When lowered the post is fully below ground and covered using the integral lid. The post is padlockable (padlock not supplied) in the raised position by first rotating the post 45° and then attaching the padlock between the post to the lid.

The Square RetractaPost is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Shown is the 70mm x 70mm version of the Square RetractaPost with optional Red & White chevron reflective label.

Product Range

Order Code	Description	Lift-up Weight	Weight
138 130 361	60mm x 60mm (Galvanised)	5.4kg	18.4kg
138 130 366	60mm x 60mm (Galvanised and Colour)	5.4kg	18.4kg
138 130 401	70mm x 70mm (Galvanised)	6.2kg	26.0kg
138 130 404	70mm x 70mm (Galvanised and Colour)	6.2kg	26.0kg

Accessories & installation parts

138 100 907	40mm Brass Padlock with 2 keys
138 150 325	Hardened Sliding Bolt Padlock with 2 keys
138 810 598	AUTOPA Red & White Chevron Reflective Label

Product details

745mm Tall (When raised).
 1010mm Below Ground.
 Galvanised or galvanised and coated finish.


Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts. An excavated hole of approximately 1,200mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete. The lid of the post should be no more than 10mm above finished ground level. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
 +44 (0)1788 550556

AUTOPA Limited
 Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103