

Distributed by:

Reduction Revolution Pty Ltd www.reductionrevolution.com.au/LED



SmartBright Road

BRP131 LED125/NW 100W 220-240V DM ANZ

12500 lm - 100 W - 4000 K

The SmartBright road is ideal for new streets and for renovating existing installations: this affordable range of lighting solutions combines clean, high-quality light with significant energy savings and reduced maintenance.

Product data

General information	
Lamp colour code	Neutral white
Driver included	Yes
Optical cover/lens type	TT [Transparent bowl with transparent cover]
Control interface	-
Connection	SI [Screw connection block]
Cable	Cable 0.5 m without plug
Protection class IEC	Safety class I (I)
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
Operating and electrical	
Input Voltage	220-240 V
Input frequency	50 or 60 Hz
Inrush current	15 A
Power factor (min.)	0.9
Controls and dimming	
Dimmable	No
	·

Housing material	Aluminium	
Optical cover/lens material	Polycarbonate	
Overall length	454 mm	
Overall width	278 mm	
Overall height	85 mm	
Effective projected area	0.11 m²	
Colour	Grey	
Approval and application		
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	12500 lm	
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	130 lm/W	
Lamp colour temperature	4000 K	
Colour Rendering Index	>70	
Initial chromaticity	7	
Initial input power	100 W	

Datasheet, 2022, September 7 data subject to change

Mechanical and housing

SmartBright Road

Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-40 to +50 °C
Product data	
Full product code	871951454805300
Order product name	BRP131 LED125/NW 100W 220-240V DM ANZ
EAN/UPC – product	8719514548053

Order code	911401692207
Local order code	BRP131100WNW
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401692207
Net Weight (Piece)	3.290 kg







Dimensional drawing





BRP131 LED125/NW 100W 220-240V DM ANZ

