



Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au/LED

SmartBright Floodlight G2 BVP151

BVP151 LED24/NW PSU 20W SWB G2 GM

SmartBright Floodlight G3 BVP151 - 2400 lm - 20 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.



Product data

General information	
Lamp colour code	840 neutral white
Driver included	Yes
Optical cover/lens type	G [Glass]
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	-
Operating and electrical	
Input Voltage	220-240 V
Input frequency	50 or 60 Hz
Inrush current	1.1 A
Power factor (min.)	0.95

Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing material	Aluminium die-cast
Optical cover/lens material	Tempered glass
Overall length	97 mm
Overall width	130 mm
Overall height	25.5 mm
Effective projected area	0.008 m ²
Colour	Aluminium and Grey
Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2400 lm

SmartBright Floodlight G2 BVP151

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	20 W
Power consumption tolerance	+/-10%

Application conditions

Ambient temperature range	-25 to +40 °C
---------------------------	---------------

Product data

Full product code	871951453403299
-------------------	-----------------

Order product name	BVP151 LED24/NW PSU 20W SWB G2 GM
EAN/UPC – product	8719514534032
Order code	911401852183
Local order code	BVP151L50N20W
SAP numerator – quantity per pack	1
Numerator – packs per outer box	24
SAP material	911401852183
Copy Net Weight (Piece)	0.340 kg

