

Distributed by: Reduction Revolution Pty Ltd www.reductionrevolution.com.au/LED



SmartBright Floodlight G2 BVP151

BVP151 LED180/NW PSU 150W SWB G2 GM

SmartBright Floodlight G3 BVP151 - 18000 lm - 150 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

Product data

840 neutral white
Yes
G [Glass]
-
Flying leads/wires
Cable 1.0 m without plug 3-pole
Safety class I (I)
NO [-]
-
220-240 V
50 or 60 Hz
4.16 A
0.95

Controls and dimming		
Dimmable	No	
Mechanical and housing		
Housing material	Aluminium die-cast	
Optical cover/lens material	Tempered glass	
Overall length	282 mm	
Overall width	409 mm	
Overall height	34.5 mm	
Effective projected area	0.077 m²	
Colour	Aluminium and Grey	
Approval and application		
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Initial performance (IEC compliant)		
Initial luminous flux (system flux)	18000 lm	

SmartBright Floodlight G2 BVP151


Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	150 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-25 to +40 °C
Product data	
Full product code	871951453398199

Order product name	BVP151 LED180/NW PSU 150W SWB G2 GM
EAN/UPC - product	8719514533981
Order code	911401857183
Local order code	BVP151L50N150W
SAP numerator – quantity per pack	1
Numerator – packs per outer box	4
SAP material	911401857183
Copy Net Weight (Piece)	2.740 kg





Dimensional drawing



BVP151 LED180/NW PSU 150W SWB G2 GM

