

# SmartBright Floodlight G2 BVP151

## BVP151 LED240/NW PSU 200W SWB G2 GM

SmartBright Floodlight G3 BVP151 - 24000 lm - 200 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

#### **Product data**

**PHILIPS** 

Lighting

General information	
Lamp colour code	840 neutral white
Driver included	Yes
Optical cover/lens type	G [ Glass]
Control interface	_
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I (I)
Flammability mark	NO [ -]
CE mark	-

#### Operating and electrical

Input Voltage	220-240 V
Input frequency	50 or 60 Hz
Inrush current	4.38 A
Power factor (min.)	0.95

Controls and dimming			
Dimmable	No		
Mechanical and housing			
Housing material	Aluminium die-cast		
Optical cover/lens material	Tempered glass		
Overall length	336 mm		
Overall width	482 mm		
Overall height	37.7 mm		
Effective projected area	0.112 m²		
Colour	Aluminium and Grey		
Approval and application			
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]		
Mech. impact protection code	IK08 [ 5 J vandal-protected]		
Initial performance (IEC compliant)			
Initial luminous flux (system flux)	24000 lm		


### SmartBright Floodlight G2 BVP151

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	200 W
Power consumption tolerance	+/-10%
Application conditions	
Ambient temperature range	-25 to +40 °C
Product data	

Full product code

871951453397499

#### **Dimensional drawing**



BVP151 LED240/NW PSU 200W SWB G2 GM



© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

Distributed by: Reduction Revolution Pty Ltd www.reductionrevolution.com.au/LED

Order product name	BVP151 LED240/NW PSU 200W SWB G2 GM
EAN/UPC – product	8719514533974
Order code	911401858183
Local order code	BVP151L50N200W
SAP numerator - quantity per pack	1
Numerator – packs per outer box	4
SAP material	911401858183
Copy Net Weight (Piece)	4.160 kg

