

Distributed by: Reduction Revolution Pty Ltd www.reductionrevolution.com.au/LED



SmartBright Floodlight G2 BVP151

BVP151 LED24/NW PSU 20W SWB MDU G2 GM

SmartBright Floodlight G2 BVP151 - 2400 lm - 20 W - 4000 K

The SmartBright G2 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

Product data

General information	
Light source color	840 neutral white
Driver included	Yes
Optical cover/lens type	Glass
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I
Flammability mark	-
CE mark	-
Operating and electrical	
Input Voltage	220-240 V
Input Frequency	50 or 60 Hz
Inrush current	1.1 A
Power Factor (Min)	0.8

Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Aluminum die-cast
Optical cover/lens material	Tempered glass
Overall length	97 mm
Overall width	172 mm
Overall height	52 mm
Effective projected area	0.008 m²
Color	Aluminum and gray
Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	2400 lm

Datasheet, 2022, August 13 data subject to change

SmartBright Floodlight G2 BVP151


Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	20 W
Power consumption tolerance	+/-10%

Order product name	BVP151 LED24/NW PSU 20W SWB MDU G2 GM
EAN/UPC - Product	8719514544819
Order code	911401881683
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401881683
Net Weight (Piece)	0.370 kg

rower consumption toterance	1/-1070
Application conditions	
Ambient temperature range	-25 to +40 °C
Product data	
Full product code	871951454481999



Dimensional drawing



BVP151 LED24/NW PSU 20W SWB MDU G2 GM

