

Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au/LED



# SmartBright Floodlight G3 BVP151

## BVP151 LED60/NW PSU 50W SWB MDU G2 GM

SmartBright Floodlight G3 BVP151 - 6000 lm - 50 W - 4000 K

The SmartBright G3 LED Floodlight features best-in-class technology to deliver high lumen efficacy with a long lifetime and reliable design. The asymmetrical optical distribution improves the light effect. The product is an ideal solution for most floodlight applications.

#### **Product data**

General Information	
Lamp colour code	840 neutral white
Driver included	Yes
Optical cover/lens type	G [ Glass]
Control interface	-
Connection	Flying leads/wires
Cable	Cable 1.0 m without plug 3-pole
Protection class IEC	Safety class I (I)
Flammability mark	NO [ -]
CE mark	-
Operating and Electrical	
Input Voltage	220-240 V
Input frequency	50 or 60 Hz
Inrush current	1.68 A
Power factor (min.)	0.9

Controls and Dimming		
Dimmable	No	
Mechanical and Housing		
Housing material	Aluminium die-cast	
Optical cover/lens material	Glass	
Overall length	173 mm	
Overall width	263 mm	
Overall height	53 mm	
Effective projected area	0.028 m²	
Colour	Aluminium and Grey	
Approval and Application		
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK07 [ 2 J reinforced]	
Initial Performance (IEC Compliant)		
Initial luminous flux (system flux)	6000 lm	
	·	

Datasheet, 2022, February 16 data subject to change

# SmartBright Floodlight G3 BVP151

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	120 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	>80
Initial chromaticity	(0.380, 0.380) SDCM <5
Initial input power	50 W
Power consumption tolerance	+/-10%

Order product name	oduct name BVP151 LED60/NW PSU 50W SWB MDU G2 GM	
EAN/UPC – product	8719514544758	
Order code	911401882283	
SAP numerator – quantity per pack	1	
Numerator – packs per outer box	16	
SAP material	911401882283	
SAP net weight (piece)	0.880 kg	


Application Conditions		
Ambient temperature range	-25 to +40 °C	
Product Data		

871951454475899



### Dimensional drawing

Full product code



BVP151 LED60/NW PSU 50W SWB MDU G2 GM

