



SMART REMOTE PRO

UNIVERSAL POWER SAVING AC REMOTE CONTROL

Regain complete control of your air conditioning costs with the
Aircon Off Smart Remote PRO!

The most advanced energy saving universal remote in the world.



SET UP AND INSTRUCTION MANUAL

V12.10.18

Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au

Smart Remote Pro Set Up & Instruction Manual

Index

- 3 Smart Remote Pro Features**
- 4-5 Setting Up the Smart Remote Pro**
 - Installing Batteries**
 - How To Unlock the Set Up Function Keypad**
 - How to Set the Min & Max Temperature Settings**
- 5 How To Set Up the Placebo Effect Function**
- 6 How to Pair the Smart Remote Pro with your AC**
- 7-8 How to Use the “Off” Timers**
- 8 Changing the Display between Celsius and Fahrenheit**
- 9 Smart Remote Pro Operating Notes**
- 10 Troubleshooting**
- 11-12 Smart Remote Pairing Code List**

Smart Remote PRO Features:

Please read this manual carefully before setting up your Aircon Off Smart Remote Pro.

Tamperproof Keypad

Access Code Lock prevents unauthorised access to the Set Up Function. Once unlocked Fast Pairing with any AC is reliable, quick and efficient. See printed manual with remote for details.

Directly input the AC Brand Pairing Code
(found on the back of this card) using the numeric keypad
(Alternatively use the unique Auto-Search function).

Energy Saving

The Energy Saving Features of this remote will work with any AC.

Programmable Temperature Ranges

The Smart Remote Pro is preset to allow the AC to operate at an energy saving 23-30 ° for Cooling and 17-23° for Heating. By using the Set Up Function you can change these temperature ranges if required. It is possible to select any range between 17°-30°, separately for Heat and Cool. For example you may prefer 22-30 for cool and 17-21 for heat.

Placebo Effect™

The Placebo Effect means that the Smart Remote Pro can be set up so that the AC appears to operate with a wider choice of temperatures than the owner settings allow. This guarantees economic and efficient operation of the AC and creates power savings without generating negative feedback from users

For example: In Cooling Mode with the Smart Remote Pro programmed to display a 5° Placebo Effect and with the minimum temperature of the Cool range set to 23°. The user will see the display on the remote scroll all the way down to 18°, with corresponding beeps from the AC, however the AC will never actually operate lower than 23°. This feature guarantees economic operation of the AC and creates power savings without generating negative feedback from users.

Optional Off Timers

Optional Countdown Timer. The remote will transmit the Power Off signal to the AC after a pre programmed number of hours (0-24hours). This timer will restart every time the AC is turned on. Optional Daily Off Timer. The remote will transmit the Power Off signal every day at the pre programmed time, 7 days a week.

Battery Security

Fitting the security screw (supplied) to the battery cover will prevent inadvertent battery removal.

Other Features

The Aircon Off Smart Remote Pro has the full range of features you would expect to see on a standard remote, including, Backlit LCD Screen, mode, fan, swing, room temperature display and a choice of Celsius or Fahrenheit. Also a Smart Button "Fast Start" function for "Instant Cooling" and "Instant Heating" (The room temperature display is disabled when the placebo effect is activated.)

SETTING UP THE SMART REMOTE PRO

Installing Batteries

Remove the battery cover on the back of the Smart Remote Pro. Insert two AAA (VM-4, R03) batteries. Should the remote not operate, Slide down the keypad cover and use a pen or a point to press hold and release the 'RESET" button. This will reboot the remote without losing settings. (Also Refer to the Operating notes and Troubleshooting Section at the end of this guide)
To make battery compartment tamperproof, fit security screw in battery cover plate.

How to set the Minimum and Maximum Temperature Settings

The Smart Remote Pro is supplied with default temperature operating settings of 23°-30° for Cooling Mode and 17° -23° for Heating Mode. It is possible to adjust these as required. If required the temperature ranges can be changed to any value between 17° – 30° for each Mode. (Eg. 23°-29° for cooling and 18°-21° for Heating). The minimum and maximum values for a range must be at least one degree apart.

How to Set Minimum Temperature for Cool Mode.

If necessary unlock the Set Up Function.

1. Simultaneously press both the "SELECT" button & the "TEMP –" (Down) " button for 3 seconds, screen will flash "Lo", then release.
2. Press and release "iCOOL" button. The "COOL" symbol will flash. Then enter chosen minimum temperature for Cool mode by using the Temp "+" & "-" buttons.
3. Press and release the OK/ENTER button to lock it in.

How to Set Maximum Temperature for Cool Mode.

If necessary unlock the Set Up Function.

1. Simultaneously press both the "SELECT" button (S) & the "TEMP +" (Up)" button (next to Blue Power Button). After 3 seconds, the screen will flash "Hi", then release.
2. Press and release "iCOOL" Button. The "COOL" symbol will flash. Then enter chosen maximum temperature for Cool mode by using the Temp "+" & "-" buttons
3. Press and release the "OK/ENTER" button to lock it in.

How to Set Maximum Temperature for Heat Mode.

If necessary unlock the Set Up Function.

1. Simultaneously press both the “SELECT” button & the “TEMP +” (Up) button for 3 seconds. The screen will flash “Hi”, then release.
2. Press and release “iHEAT” button. The “HEAT” symbol will flash. Then enter chosen maximum temperature for Heat Mode by using the Temp “+” & “-” buttons.
3. Press and release the “OK/ENTER” button to lock it in.

How to Set Minimum Temperature for Heat Mode

If necessary unlock the Set Up Function.

1. Simultaneously press both the “SELECT” button & the “TEMP -” (Down) button for 3 seconds. The screen will flash “Lo”, then release.
2. Press and release “iHEAT” button. The “HEAT” symbol will flash. Then enter chosen Minimum temperature for Heat Mode by using the Temp “+” & “-” buttons.
3. Press and release the “OK/ENTER” button to lock it in.

How to Set the Placebo Effect Function

The Placebo Effect is added to the Minimum temperature setting for Cool and Maximum temperature setting for Heat.

For Example: In COOL mode If the minimum temperature is set by the owner to 23° and the Placebo Effect is set to 5°. The Smart Remote display will scroll down to 18° but AC will actually still be operating no lower than 23°.

In HEAT mode if the max temp is set to 21° and the Placebo Effect is set to 5°: The Smart Remote display will scroll up to 26° but the AC will actually still be operating no higher than 21°.

The default setting for the Placebo Effect is 0° (Off), during set up this can be adjusted between 0 and 5. A separate Placebo Effect can be set for Heat and Cool.

How to Set the Placebo Effect for Cool Mode.

If necessary unlock the Set Up Function.

1. Simultaneously press the “SELECT” button & the “Number 8” button for 3 seconds. The screen will flash “PL” and “COOL” symbols, then release.
2. Using the Temp “Up” & “Down” buttons enter the chosen number of Placebo Effect degrees.
3. Press the “OK/ENTER” button to lock it in.

How to Set Placebo Effect for Heat Mode

If necessary unlock the Set Up Function.

1. Simultaneously press the “SELECT” button & the “Number 7” button for 3 seconds. The screen will flash “PL” and “HEAT” symbols, then release.
2. Using the Temp “Up” & “Down” buttons enter the chosen number of Placebo Effect degrees
3. Press the “OK/ENTER” button to lock it in.

How to Pair the Smart Remote Pro with your Air Conditioner

The Smart Remote Pairing Code list on page 7 lists all major brands of air conditioners and the associated Smart Remote Brand Codes. These Smart Remote Codes do not relate to specific air conditioner model numbers. The Smart Remote is compatible with any air conditioner.

If your brand **is listed**, use the **Direct Code Input Method**.

If your brand **is not listed** or if the listed codes are not successful with your AC, then use the **Auto Search function** to find the matching code.

This is a link to Smart Remote Pairing information and videos:

<https://www.airconoff.com.au/smart-remote-setup>

How to Use Direct Code Input Method. When your AC IS LISTED on the brand code list

1. From the Code Table, select the correct codes for your brand. Start with the first code, if this does not operate your AC, try the second code and so on.

Note: There are often many possible codes. Each code in the list is separated by a comma", or hyphen"-". Commas separate individual codes and hyphens show a range of codes. For example: 0200-0205 this means 0200, 0201, 0202, 0203, 0204, 0205.

2. If necessary unlock the Set Up Function. With the AC on standby but not running (not blowing air). Press the "SELECT" key, the Model Code display will flash on the LCD. Using the keypad enter the selected 4 digit code. Press each digit in turn. The Smart Remote accepts the code automatically. To test a code use the Blue Power Button. If it turns the AC "On", try other function keys. If the AC does not turn "On" or if other functions do not work correctly, then try another code. To input another code, press the "SELECT" key again and enter the new code. Repeat this until all functions work correctly.

How to use Smart Remote Brand Code Auto-Search (When Listed Codes Don't Work or the Brand is Not Listed)

1. If necessary unlock the Set Up Function. With the AC on standby but not running (not blowing air). Aim the Smart Remote at your air conditioner. Press and hold the "SELECT" key for 5 seconds and then release.

The Smart Remote will go into auto-search mode and will emit a continuous signal. The code numbers on the LCD display will flash and then steadily increase. Keep the remote pointing at the AC. (If the code numbers start too high, use the "TEMP Up & Down" keys to scroll to the code that you want to start the Auto-Search from.) When the AC receives a signal it recognises it will make a beep. Immediately press any key to stop the count on that code. If you don't stop the count in time you will need to scroll back to the lower code number required

2. Test the code fully by trying all normal function keys. If they do not work correctly with the AC you have not found a totally compatible code. Repeat steps 1 and 2 until a completely correct code is found and the AC operates normally.

How to Use the “Off” Timers

This remote operates by direct line of sight to the AC wall unit. For the timers to operate correctly the remote must be pointing at the AC at the exact moment it sends the “Off” signal. Test the correct operation of the On Off signal before fixing the wall bracket in place.

We recommend the use of the Smart Mount upgrade to ensure that the remote is always correctly positioned.

www.airconoff.com.au/aircon-off-smart-mount.

How to Set the Automatic Countdown “Off” Timer

The remote will transmit the “Power Off” signal to the AC after a pre programmed number of hours (1-24). This timer will restart every time the AC is turned on, and a signal will be sent to turn “Off” the AC after the programmed number of hours have elapsed.

1. If necessary unlock the Set Up Function. Press and hold “Number 8” button for 4 seconds. The screen will flash 01 hr and ON.
2. Using the “Time +” or “Time –“ buttons select the required number of hours.
3. Press the OK/ENTER button to lock it in.
4. When the AC is running the LCD display will show ON to indicate the countdown timer is operating.

How to Cancel the Automatic Count Down “Off” Timer

1. Press and hold “Number 8” button for 4 seconds.
2. The screen will flash OFF to show the Count Down Timer is cancelled.

How to Set the Daily “Time of Day Off” Timer

The remote will transmit the Power “Off” signal at the pre programmed time of day, 7 days a week.

Step 1 Turn On the Clock

In order to save battery life the clock function should only be switched on if the Time of Day Off Timer is being used.

1. To turn the clock “On”, press and hold the "Clock" button for 4 seconds. The screen will show AM 00.00 and the “Clock” symbol. Then release.
2. Press and release the “Clock” button again and the time display will flash
3. Adjust the "Time + or Time -" buttons, to set the current time.
4. Press the "Clock" button again, the time signal will stop flashing, the time is now set.

When the batteries run down and need to be replaced or if the batteries are removed for any reason the Clock will need to be reset. In order to prevent accidental battery removal, secure the battery compartment using the security screw provided.

Step 2 Set the Daily Off Timer

1. Press and hold “Number 8 ” button for 4 seconds.
2. The screen will show “PM 0.00 hr” and ON
3. Using the Time + or Time -- buttons select the required “Off” time
4. Press OK/ENTER button to lock it in

When the AC is running the LCD display will show ON above the clock symbol to indicate the Time of Day Off timer is operating.

How to Cancel the Daily Off Timer and Turn Off the Clock

1. Press and hold “Clock” button for 4 seconds.
2. The screen will show “OFF” and the clock will disappear to show the clock is turned off and the Time of Day Off Timer is cancelled.

Changing the display between Celsius and Fahrenheit.

With the Set Up Function unlocked, press and release the "C/F" button. The display will change between Fahrenheit and Celsius.

Smart Remote Pro Operating Notes

Mode Symbols



Set Up Function Lock

The Settings Lock prevents unauthorised changes. (Tampering). The Settings Lock prevents unauthorised changes. (Tampering). The Set Up Function will automatically lock after 3 minutes of no activity.

Timer Operations

This remote operates by direct line of sight to the AC wall unit. For the timers to operate correctly the remote must be pointing at the AC at the exact moment the off signal is sent. For Timer Operations we recommend the use of the Smart Mount upgrade to ensure that the remote is always correctly positioned. www.airconoff.com.au/aircon-off-smart-mount.

Battery Security when using Time of Day Timer.

When using the Time of Day Timer: If the batteries are removed/changed the clock will need to be reset in order for the timer to work correctly. In order to prevent accidental battery removal, secure the battery compartment cover using the security screw provided.

Batteries

Always use high quality Alkaline batteries., If it is not intended to use the Smart Remote Pro for an extended period, remove the batteries to avoid battery leakage which will damage the unit.

Optional "Factory Set and Locked"

If the Smart Remote Pro has been supplied "Factory Set and Locked", the Temperature Range and Placebo Function are preset to special order and are not adjustable.

Use of "Instant Cooling"/"Instant Heating"

Pressing the "Intelligent Cooling" button will turn on the AC directly into cooling mode.

Pressing the "Intelligent Heating" button will turn on the AC directly into heating mode.

In both modes, the AC will automatically select heating and cooling at a comfortable, economic temperature. It is possible for a user to adjust the temperature by using the "Temp.+" "Temp.-" keys. (Users can still only access temperatures as per the settings preset by the owner).

Troubleshooting

Blank Screen. Dim Screen, or if your Remote is not Responding

First change batteries. (Never mix new and old batteries together) If after changing batteries the screen stays blank, the remote needs to be reset/rebooted. Reset the unit by pressing the recessed “RESET” button on the keypad with a blunt point like a pencil.

Do **not** use a sharp point like a pin. The remote will not lose its settings when you change batteries or if you use the reset button, but you will need to reset the clock if required to operate the Time of Day Off Timer.

Incorrect LCD Display or Unusual Operation.

Reset the unit by pressing the recessed “RESET” button on the keypad with a blunt point like a pencil. Do not use a sharp point like a pin. The remote will not lose its settings when you use the reset button but you will need to reset the clock if required to operate the Time of Day Off Timer.

My Air Conditioner has a temperature readout on the front that is different to the Remote Placebo Display

Some air conditioners have a digital LED temperature readout that shows the temperature setpoint of the airconditioner. This will of course conflict with the Placebo setting readout on the remote control. Therefore to use the Placebo effect on AC's like this, you will need to block out this display on the AC. Lift the front cover of the AC, cover up the temperature readout screen with Black Gaffer Tape (or similar) and then close the cover again.

During Set Up if the Smart Remote is not operating the AC correctly or if the AC won't turn “Off”

Some codes are quite similar. During Set Up the AC may recognise a “partial” Code and you may find that only some functions will work correctly. In that case continue pairing steps 1 and 2 until the correct code is found. If a particular code turns the AC ‘On’ but not ‘Off’ it may be necessary to turn the AC “Off” by using the AC’s original remote if available. Alternatively turn the unit off by using the Emergency “Off” push button (usually located under the filter cover on the front of the AC wall unit. (Please refer to your AC owners manual). Or you may turn the power supply to the AC “Off” and “On” again via the mains supply or circuit breaker. Once the AC is back in standby mode continue the code search. Repeat Pairing steps 1 and 2 until the correct code is found and the AC works normally.

If this problem occurs and you are using Auto Search you may have not stopped the auto search quick enough after the AC switched on. Retrace your steps back a few codes and try again.

During Set Up Keypad Inputs Not Working

If the keypad does not respond to a setting input it may be because the keypad has become locked, If necessary unlock the Set Up Function again.

During Set Up. If only certain functions are available

If the Smart Remote Pro has been supplied with the Option “Factory Set and Locked” the Temperature Range and Placebo Function are preset and not adjustable. Only the Pairing Function will be available.

UNIVERSAL POWER SAVING AC REMOTE CONTROL

| BRAND | Smart Remote Code | BRAND | Smart Remote Code |
|----------------|--|----------------|---|
| ACSON | 0234 | KANGLI | 0374, 0375, 0654, 1399,1910 |
| AGREE | 0107, 0108 | KELON | 0282-0287, 0473,0485-0488 |
| AGER | 0489, 0785 | KELVINATOR | 0151, 0197, 0203, 0619, 1007, 1024, 1133 |
| AIRWELL | 0529, 0555,0556 | KLIMATAIR | 0225, 0226, 0452, 0737-0738,1761 |
| ALPIN | 0252, 0253, 0617, 0764, 0765, 1277, 1789 | KOLIN | 0416-0418, 1441, 1952 |
| ARENA | 0206, 0212, 0229, 0718, 0724, 0741 | KONKA | 0397, 0457-0459, 1933 |
| ARLEC | 0202 | LENNOX | 0234,0260-0265,0522,0523,0568,0773, 0582,1289,1976 |
| ATD | 0169, 0170 | LG | 0197-0200, 0504-0514, 0567, 0572, 0710, 1026,1733 |
| AUCMA | 0288-0296, 0462, 0802, 0807, 0901, 1313, 1998 | LIANGYU | 0233, 0451, 0745,1257 |
| AUSSIE AIR | 0809 | LITTLE DUCK | 0015-0020, 0528-0531, 1043 |
| AUX | 0297-0300, 0451, 0474, 0475, 0810-0812, 1987 | LOREN-SEBO | 0255, 0471, 0472,0767 |
| BANSHEN | 0264, 1288,1800 | LUXAIRE | 0297 |
| BLUEWAY | 0300 | MACQUAY | 0234-0237, 0465, 0468, 0472, 0587, 0746-0747, 1773 |
| BOERKA | 0383, 0434, 0436, 0437, 0522, 0948, 1407, 1972 | MICOM | 0415, 0927, 1951 |
| CARRIER | 0203-0209, 0235,0456-0458, 0482-0486, 0563-0565, 0590 1933 | MIDEA | 0260-0265, 0522, 0523, 0568, 0773, 0582, 1289,1976 |
| CELESTIAL | 0108, 0307 | MISTRAL | 0237 |
| CHANGHONG | 0301-0308, 0627, 0813-0815, 0820,1843 | MITSUBISHI | 0001-0045, 0476-0479, 0515, 0522, 0523 0556, 0567, 0568, 0582, 0616, 0695,1502 |
| CHIGO | 0379-0382, 0489, 0515, 0890-0894,1403,1916 | MITSUBISHI HVY | 0043, 0568, 0616 |
| CHOFU | 0184-0187, 0581, 0696,0698,1209,1723 | NEC NATIONAL | 0138-0154, 0200 0483, 0490-0492, 0653, 0658-0666, |
| CHUNLAN | 0345-0350, 0450, 0453, 0545-0546, 0862,1373 | NORITZ | 0431, 1455 |
| CLIMA VENETA | 0572 | OMEGA | 0559 |
| CORONA | 0155-0163, 0459,0561, 0667, 0675, 1180, 1995 | OMNI | 0146, 0262 |
| CONIA | 0570, 0571, 0806,0812,0861 | PANASONIC | 0138-0154, 0483, 0490-0492, 0653, 0658-0666,1507 0378, |
| CONROWA | 0377, 1401,1913 | PANDA | 0505, 0509, 0763,0890 |
| CONSUL | 0463, 0718, 0734,0975 | PHILCO | 0210, 0211, 0487-0490,1746 |
| COOLINE | 0187, 0206 | POLAR ICE | 0570-0572 |
| COUNTRYAIR | 0560 | PROTON | 0421-0423, 0933, 0934, 0956,1958 |
| DERBY | 0311 | RAYBO | 0362-0367, 1386, 1898 |
| DAEWOO | 0203-0209, 0406, 0715-0718, 1942 | RINNAI | 0297-0300, 0451, 0474, 0475, 0810-0812, 1987 0369, |
| DAIKIN | 0171-0183, 0566, 0567, 0574, 0577, 0583, 0685, 0693-0695, | ROWA | 0438, 0439, 0494, 0527, 0531, 1393 |
| DE LONGHI | 0151, 0232, 0482, 1707 | SABRO | 0435, 0506-0508, 1018, 1020,1971 |
| DEC/ DHL | 0504, 0592 | SAIJO DENKI | 0212-0215, 0721-0726, 1750 |
| DAVINCI | 0298, 0400 | SAMPO | 0424-0426, 1448, 1961 |
| DL | 0302 | SAMSUNG | 0188-0196, 0503, 0516, 0518, 0700-0707, 1015, 1726 |
| DOCTOR | 0221, 0449, 1245,1985 | SANYO | 0046-0095, 0519, 0530, 0558-0562, 0598-0605,1582 0254, |
| DONGBAO | 0355-0361, 1385, 1891 | SASUKI | 0470, 0654, 0766,1494 |
| DONGXINBAO | 0413, 0891,0925, 1654 | SHANGLING | 0384-0388, 0444, 0445,1980 |
| EMAILAIR | 0127, 0553, 0556,0558, 0639, 0642 | SHANXING | 0392, 0449, 1416,1985 |
| ELECTRA | 0553, 0557 | SHARP | 0096-0106, 0525, 0542,0608-0609, 0617, 0631, 1640 |
| ELECTROLUX | 0216-0220, 0569, 0728-0733,1245,1752 | SHENGFENG | 0376, 0406-0480, 1504,1912 |
| FEDDERS | 0498,0499, 0500, 0528 | SHINCO | 0351-0354, 0454-0456, 1887 |
| FRESTECH | 0277, 0495-0497,0519, 0520, 0665, 0789 | SHUANGLU | 0376, 0404-0407, 0480,1941 |
| FUJIN | 0002 | SHUAIKANG | 0288, 0587,0800 |
| FUJITA | 0265, 0297 | SONGGE | 0428, 0429, 1453,1964 |
| FUJITSU | 0127-0137, 0464, 0509, 0522-0554, 0640, 0648, 1152 | SOVA | 0409, 0410, 0921,1434 |
| FUNAI | 0430, 0481, 1505,1966 | SUMMER | 0427, 0672,1451 |
| GALANZ | 0371, 0372, 0521, 0883,1908 | SUNDURG | 0257, 0505, 1017,1793 |
| GE | 0047 | STARWAY | 0714, 0345,0859 |
| GENERAL | 0128-0136, 0639, 0976,1161 | SWAN | 0434, 0477, 0516, 0524, 0732, 0946 |
| GUQIAO | 0244, 0291, 0491, 1268,1827 | TADIRAN | 0246-0251, 0758, 0762,1275 |
| GLEE | 0398, 0399, 0521, 0910,1935 | TATUNG | 0419, 0420, 0931-0932,1955 |
| GOLDSTAR | 0201, 0466-0469, 0713, 0978-0980, 1737 | TCL | 0273-0281, 0570, 0786-0793,1305 |
| GREE | 0309-0316, 0482, 0512,0513 | TECO | 0008, 0108, 0109,1007, 0232, 0256,0473-0475,0768,1792 |
| HAIER | 0266-0272, 0453-0455, 0538, 0539, 0778-0781 | TIANDI | 0415, 0643,1439 |
| HISENSE | 0332-0335, 0340, 0505, 0506, 0517, 0671, 0681, 0847, 1359, | TITANIUM | 0339 |
| HITACHI | 0118-0126, 0178, 0500, 0501,0605, 0630-0631, 0637, 1145 | TOSHIBA | 0107-0117, 0489, 0619-0630, 1001,1643 |
| HOFWELL/HELLER | 0107, 0282, 0289,0811 | TRANE | 0227-0232, 0739, 1768 |
| HOMEMAKERS | 0297-0300, 0451, 0810, 0960,0963 | | |

| | | | |
|-----------------|---|---------------------|--|
| HUABAO | 0336-0344, 0848-0855, 1360,1878 | UNI-AIR | 0222-0224, 0450, 0734-0735, 1986 |
| HUAKE | 0408, 0493-0498, 0920,1944 | WAN BAO | 0138-0152, 0666, 0905, 0995,1177 |
| HUAMEI | 0402, 0460-0465, 1426,1999 | WEILI | 0393-0396, 0907-0908, 1420,1929 |
| HUALING | 0317-0325, 0452, 0964 | WHIRLPOOL | 0164-0170, 0502, 0677-0678, 1760 |
| HUIFENG | 0370, 0882, 0568, 0441-0443, 1392, 1979 | | |
| HUIKANG | | | |
| HYUNDAI | 0202, 0433, 0480, 0550, 0551, 0609, 1226,1969 | WINIA | 0481, 0550,0993 |
| JDC | 0373, 0440, 0952,1909 | XILENG | 0411, 0412, 0923-0924,1947 |
| JET AIR | 0169, 0170 | YANGZI(YAIR) | 0403, 0488-0493, 0915 |
| JIANGNAN | 0432, 1456 | YINYAN | 258, 259, 326-331, 0770, 0838-0844 |
| JINDA | 0414, 0926, 1950 | YORK | 0002, 0107, 0238-0243, 0501, 0502, 0573, 1266 |
| JINSONG | 0389-0391, 0446-0448, 0757,1984 | ZHEN BAO | 0129-0137, 1151, 1488, 1664, |
| JOHSON | 0245, 0492, 1269,1516 | | |

Pairing Code Brand List :

Each brand on the list can have several Smart Remote codes. Each code in the list is separated by a comma", " or hyphen"-". Commas separate individual codes, hyphens show a range of codes.

For example: 0200 - 0205 means 0200, 0201, 0202, 0203, 0204, 0205.

For unlisted brands use the Smart Remotes unique
AC Brand 'Autosearch' Function that will find the code for you.

Smart Remote is guaranteed compatible or your money back* Smart Remote Set Up and Pairing Video
Help can be found at

<http://www.airconoff.com.au/smart-remote-setup>

Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au