



# FLIR ONE® EDGE PRO

Thermal cameras with wireless connectivity for iOS® and Android™ smart devices



## Key Features:

- Wirelessly connects to your smart device for convenient inspections
- Unrivaled thermal image clarity with MSX® (Multi-Spectral Dynamic Imaging)
- Use the FLIR ONE app for efficient thermal analysis, and seamlessly connect to the FLIR Ignite™ cloud solution

## Main Applications:

- Identifying and locating moisture intrusion and insulation deficiencies
- Diagnosing issues in HVAC/R inspections
- Identifying abnormalities in electrical and mechanical components

[www.flir.com/flir-one](http://www.flir.com/flir-one)

## SPECIFICATIONS

	FLIR ONE Edge Pro
Thermal resolution	160 × 120 (19,200 pixels)
Object temperature range(s)	-20°C to 120°C (-4°F to 248°F) 0°C to 400°C (32°F to 752°F)
VividIR image enhancement	Yes
Image presentation modes	MSX, infrared image, visual image
Live measurement analysis	Hottest, coldest, and 3 adjustable spots
Android & iOS compatibility	Yes, compatible with both iOS and Android devices
Wireless remote operation	Yes (up to 5 m from smart device)
<b>General Features</b>	
Device compatibility	iOS (version 15 and later) or Android (version 11 and later) smartphones and tablets
IP rating	IP54
Drop tested	Drop from 2 m (6.56 ft)
FLIR software compatibility	FLIR ONE app, FLIR Ignite, FLIR Thermal Studio
SDK available for app development	Yes
Thermal sensitivity	70 mK
Certifications	RoHS, CE/FCC, CEC-BC, EN62133, UL1642, WEEE 2012/19/EU
Operating temperature	-10°C to 50°C (14°F to 122°F), battery charging 0°C to 45°C (32°F to 113°F)
Storage temperature	-40°C to 70°C (-40°F to 158°F)
Size (w × h × d)	35 mm × 37.5 mm × 149 mm (1.4 in × 1.5 in × 5.9 in)
Weight (incl. battery)	153 g (5.4 oz)
Clip span	130 mm (min) / 195 mm (max)

	FLIR ONE Edge Pro
<b>Optical Data</b>	
Spectral range	8 μm to 14 μm
Visual resolution	640 × 480
HFOV / VFOV	54° ±1° / 42° ±1°
Frame rate	8.7 Hz
Focus	Fixed 30 cm – infinity
<b>Measurement</b>	
Accuracy	±3°C (5.4°F) or ±5%. Applicable 60 sec after start-up when the unit is within 15°C to 35°C (59°F to 95°F) and the scene is within 5°C to 120°C (41°F to 248°F)
Emissivity correction	Matte, Semi-Matte, Semi-Glossy, Glossy
Measurement correction	Emissivity; Reflected apparent temperature (22°C / 72°F)
Shutter	Automatic/Manual
<b>Power</b>	
Battery life	2 h 30 min
Battery charge time	60–90 min for fully charged. 15 min charging, from empty battery, gives 40 min operating time
<b>Interfaces</b>	
Wi-Fi	802.11 a/b/g/n
Bluetooth	Uses Bluetooth to set up the peer-to-peer Wi-Fi network that the camera creates to connect to the mobile device
Charging	Female USB-C (5V/1A)
Remote connection	Via Wi-Fi



# FLIR ONE® EDGE PRO

Thermal Cameras with wireless connectivity for iOS® and Android™ smart devices

## SPECIFICATIONS, CONT.

	FLIR ONE Edge Pro
<b>App</b>	
Video and image capture	Yes
File formats	Radiometric JPG, MPEG-4 (file format MOV (iOS), MP4 (Android))
Spot measurements	Hottest, Coldest, and 3 spot measurement
Adjustable MSX distance	0.3 m – infinity
Visual battery indicator	0% to 100%
<b>Radio</b>	
Wi-Fi	<ul style="list-style-type: none"><li>• Standard: 802.11 a/ac/b/g/n</li><li>• Frequency range:<ul style="list-style-type: none"><li>- 2401–2473 MHz</li><li>- 5150–5250 MHz</li></ul></li><li>• Max. output power: 15 dBm</li></ul>
Bluetooth	<ul style="list-style-type: none"><li>• Frequency range:<ul style="list-style-type: none"><li>- 2400–2484 MHz</li></ul></li><li>• Max. output power: 10 dBm</li></ul>

Apple Store FLIR Apps



Google Play Store FLIR Apps

