

PRODUCT DATASHEET

LED SST D/L TRI 7.50 W 3000 K 4000 5000 KIT GEN4

LED SUPERSTAR DOWNLIGHT TRI-COLOUR SWITCH | LED downlight with three settable color temperatures



AREAS OF APPLICATION

- Bathrooms (IP44)
- Residential interiors
- Commercial lighting

PRODUCT BENEFITS

- Easy connection thanks to Plug and Play technology

PRODUCT FEATURES

- Three light colors selectable via slide switch
- Luminous efficacy: up to 106 lm/W
- Beam angle: 90°
- Dimmable (with many common dimmers, see also www.ledvance.com.au)
- Type of protection, front side: IP44



Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au/LED

TECHNICAL DATA

Electrical data

Nominal wattage	7.50 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	3000/4000/5000 K
Color rendering index Ra	≥80
Light color (designation)	Warm White/Cool White/Daylight
Luminous flux	750/850/820 lm
Luminous efficacy	85/96/93 lm/W

Light technical data

Beam angle	90 °
------------	------

Dimensions & weight

Diameter	114.0 mm
Height	57.5 mm
Product weight	230.00 g

Colors & materials

Body material	Polybutylene terephthalate (PBT)
Product color	White
Housing color	White

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Mounting type	Recessed
---------------	----------

Capabilities

Dimmable	Yes
Type of connection	Plug, 2 pin Australian
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP44

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075301467	Folding carton box 1	123 mm x 123 mm x 73 mm	242.00 g	1.10 dm ³
4058075301474	Shipping carton box 12	263 mm x 263 mm x 250 mm	3318.00 g	17.29 dm ³
4058075315051	Folding carton box 4	247 mm x 129 mm x 156 mm	1027.00 g	4.97 dm ³
4058075315068	Shipping carton box 24	512 mm x 405 mm x 182 mm	7069.00 g	37.74 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au/LED