ATelec **KWH METER DIN RAIL MOUNT**

NMI APPROVED

THREE PHASE - NMI APPROVED

FEATURES & BENEFITS

- NMI approved for billing applications
- Digital LCD display
- Polyphase Suitable for 1, 2 and 3 phase metering
- Tamper seal kit available
- applications.

SPECIFICATIONS

Materials:

- Housing Fire resistant ABS .
- Weatherproof rating:
- IP51
- **Display:** .
- Digital LCD Accuracy class:
- Class 1
- Insulation class:
- Class 2 .
- Maximum rated current:
- 100 Amp

- Operational current range: 0.25 - 100 Amp • Over current withstand: 1000 Amp for 0.1s Nominal voltage: 230 /415Vac Operating frequency: 50 - 60 Hz . Maximum cable capacity: 25mm² (neutral 2.5mm²) Operating temperature: -20°C to 65°C
- 1 year warranty
- Note Not suitable for solar
- Test output flash rate:
- 1000 impulses per kWh
- Power supply indicator:
- Mains power ON
- Consumption indicator:
- Flashing on load
- Conforms to:
- IEC62052-11
- IEC62053-21

Dimensions:

100mm (H) x 122mm (W) x 65mm (D) 7 Modules

Report/Certification Number	Date Issued
SGS Test Report Reference No. SHE5190301218301	5/5/2019
National Measurement Institute (NMI) 14/2/107	10/7/2019
IEC Test Report IEC 62053-21:2003, IEC62052-11:2003	12/12/2014





Code	Description	Packing	MOQ	Ctn
FKW-15120/NMI	KWH Meter - Din Rail Mount - Direct Electronic 0-100A - Three Phase - NMI Approved	1	1	30