



PRODUCT FAMILY DATASHEET

LED Oyster Tri-Colour

LED ceiling luminaires with three settable color temperatures

AREAS OF APPLICATION

- Living areas (living rooms, dining rooms, bedrooms etc.)



PRODUCT BENEFITS

- Easy and quick installation
- Slim and sleek design

PRODUCT FEATURES

- Three light colors selectable via slide switch
- Very long lifetime: up to 40,000 h
- Beam angle: 120°
- Dimmable (with many common dimmers, see also www.ledvance.com.au)



Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au

TECHNICAL DATA

Product description	Electrical data			Photometrical data		Dimensions & weight			Colors & materials		Temperatures & operating conditions
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Diameter	Height	Product weight	Body material	Product color	Ambient temperature range
OYSTER LED CEILING SLIM TRI-COLOR 12 W	12.00 W	220...240 V	50 Hz	3000/4000/5700 K	970/1100/1080 lm	250.0 mm	48.0 mm	700.00 g	Polycarbonate (PC)	White	-20...+45 °C
OYSTER LED CEILING SLIM TRI-COLOR 18 W	18.00 W	220...240 V	50 Hz	3000/4000/5700 K	1800/1710 lm	300.0 mm	40.0 mm	880.00 g	Polycarbonate (PC)	White	-20...+45 °C
OYSTER LED CEILING SLIM TRI-COLOR 25 W	25.00 W	220...240 V	50 Hz	3000/4000/5700 K	2125/2300/2250 lm	300.0 mm	40.0 mm	880.00 g	Polycarbonate (PC)	White	-20...+45 °C
OYSTER LED CEILING SLIM TRI-COLOR 25 W	25.00 W	220...240 V	50 Hz	3000/4000/5700 K	2125/2300/2250 lm	350.0 mm	40.0 mm	1200.00 g	Polycarbonate (PC)	White	-20...+45 °C
OYSTER LED CEILING SLIM TRI-COLOR 30 W	30.00 W	220...240 V	50 Hz	3000/4000/5700 K	2700/2850/2800 lm	400.0 mm	52.0 mm	1430.00 g	Polycarbonate (PC)	White	-20...+45 °C

Product description	Lifespan	Capabilities		Certificates & standards	
	Lifespan	Dimmable	Type of connection	Protection class	Type of protection
OYSTER LED CEILING SLIM TRI-COLOR 12 W	40000 h	Yes	Terminal	II	IP40
OYSTER LED CEILING SLIM TRI-COLOR 18 W	40000 h	Yes	Terminal	II	IP40
OYSTER LED CEILING SLIM TRI-COLOR 25 W	40000 h	Yes	Terminal	II	IP40
OYSTER LED CEILING SLIM TRI-COLOR 25 W	40000 h	Yes	Terminal	II	IP40
OYSTER LED CEILING SLIM TRI-COLOR 30 W	40000 h	Yes	Terminal	II	IP40

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

Distributed by:
 Reduction Revolution Pty Ltd
www.reductionrevolution.com.au

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075132528	Shipping carton box 5	318 mm x 289 mm x 292 mm	5078.00 g	26.84 dm ³
4058075132542	Shipping carton box 5	338 mm x 283 mm x 342 mm	6380.00 g	32.71 dm ³
4058075132566	Shipping carton box 5	338 mm x 283 mm x 342 mm	6380.00 g	32.71 dm ³
4058075132580	Shipping carton box 5	388 mm x 283 mm x 392 mm	8504.00 g	43.04 dm ³
4058075132603	Shipping carton box 5	383 mm x 303 mm x 311 mm	8249.00 g	36.09 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au