



Smartbright CCT/ Wattage Tunable Waterproof Bulkhead

WL020C LED SWT/SCCT AU

New Smartbright Tri Color Waterproof Bulkhead provide flexibility to customer to choose from 3 CCT and 2 wattage options before installation, based on their specific need

Product data

General Information		Number of products on MCB of 16 A type B 26	
Beam angle of light source	120 °	RoHS mark	-
Light source color	White	Operating and Electrical	
Light source replaceable	No	Input Voltage	220 to 240 V
Number of gear units	1 unit	Input Frequency	50 or 60 Hz
Driver/power unit/transformer	Power supply unit	Initial CLO power consumption	- W
Driver included	Yes	Average CLO power consumption	- W
Optic type	Beam angle 120°	Inrush current	5 A
Luminaire light beam spread	120°	Inrush time	0.42 ms
Control interface	-	Power Factor (Min)	0.9
Connection	Connection unit 3-pole	Controls and Dimming	
Cable	-	Dimmable	No
Protection class IEC	Safety class II	Mechanical and Housing	
Glow-wire test	Temperature 650 °C, duration 30 s	Housing Material	Polycarbonate
Flammability mark	-	Reflector material	-
CE mark	-	Optic material	Polycarbonate
ENEC mark	-	Distributed by: Reduction Revolution Pty Ltd	
Warranty period	5 years	www.reductionrevolution.com.au	
Constant light output	No		

Smartbright CCT/Wattage Tunable Waterproof Bulkhead

Optical cover/lens material	Polycarbonate
Fixation material	-
Optical cover/lens finish	Opal
Overall height	77 mm
Overall diameter	241 mm
Color	White

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	>80
Initial chromaticity	0.3818;0.3797
Initial input power	16 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)


Median useful life L70B50	56000 h
Median useful life L80B50	34000 h
Median useful life L90B50	16000 h

Application Conditions


Ambient temperature range	-20 to +40 °C
Maximum dim level	Not applicable

Product Data

Full product code	871016334438699
Order product name	WL020C LED SWT/SCCT AU
EAN/UPC - Product	8710163344386
Order code	911401822280
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	5
Material Nr. (12NC)	911401822280
Net Weight (Piece)	0.580 kg



Dimensional drawing



WT188C/WL020C

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.



Distributed by:
Reduction Revolution Pty Ltd
www.reductionrevolution.com.au