



ECOLITE

101 ADJUSTABLE



The perfect solution for commercial or residential applications which require a comfortable, efficient, ultra low profile and adjustable lighting solution.

Designed for maximum visual comfort, the new Ecolite 101 features a low-glare recessed LED, effectively hiding the light source from the viewer's direct line of sight. Its low glare design is complimented by its 180° gimbal design, ensuring it seamlessly integrates within your ceiling.

SKU	COLOUR	CCT
EL10X8-WH-QC	White	5CCT

SPECIFICATIONS

WATTAGE (W)	8W
BEAM ANGLE (°)	45°
UGR	<19
IP RATING	IP44 (for parts outside ceiling only) IP40 (for parts recessed in ceiling)
INPUT VOLTAGE (V)	AC220-240V
WARRANTY	36 months
CUTOUT (Ø)	90mm
DIMENSIONS	D108*H34mm
LED CHIP TYPE	COB
LUMENS (lm)	730lm
EFFICACY (lm/W)	80lm/W
CCT	5CCT Switchable (2700K + 3000K + 4000K + 5000K + 6000K)
CRI	90
LIFETIME (Hours)	50,000
COLOUR OPTIONS	White
MATERIALS/S	Die cast aluminium
DRIVER SPEC	AC220-240V external DC33-38V Triac
DRIVER TYPE	External

Please direct all enquiries and quote requests to quotes@zlights.com.au

Disclaimer: zlights. All prices are subject to change without warning; please check with your sales representative prior to ordering. While every effort has been made to ensure the accuracy of the information presented on this sheet, it is intended as a guide only. zlights will not be bound by or responsible for any errors or omissions.