FLOS

Bellhop 125 Wall - Specification Sheet
by E. Barber and J. Osgerby

Mounting	Wall
Lamp (Bulb) Description	8W, 783lm, 2700K, CRI80
Environment	Outdoor - Wet location
Dimming	No dimmable
Finish	White
Technical and Product Description	Recommended connections for in-ground installations with a 2-way terminal block 4-pole IP68 water stop on 24V side. Order separately. Painted versions are an exterior rated epoxy polyester powder coat finish for superior strength, heat and UV resistance. During installation and maintenance avoid scratching or damaging the finish as it may result in premature corrosion of metal surfaces. Avoid cleaning fixtures with corrosive chemicals as it may result in voiding the warranty. LED fixtures are highly susceptible to failure due to electrical effects from poor connections, and electrical short circuits. These are frequently caused by (a) over- voltage from primary voltage sources, (b) electrostatic discharge from the exterior environment. Ensure that all outdoor fixtures are installed on GFI circuits as required by code, and use proper surge protecting devices to avoid irreversible damages to electrical components. Bellhop Wall includes a Jbox Cover Plate

Electrical

Voltage	120
IP Rating	IP65

Physical

Construction Material	Aluminum

○ F003C21AU01-W White

Dimensional Image

0.3''   2.9''

Ø4.9''

4.9''

Ø4.9''