

Quick Set Shelf Kit for cart models R6RT / R6G / R64C

RSH6Q Model Specifications		Your RSH6Q shipping box should contain the following part:			
Length (Extended)	39.25″	4 x	⁵⁄‰″ low profile socket head screw	6 x	swivel tab
Width	16″	4 x	round support tubes	6 x	short Allen bolt
Weight	14.3 lbs.	1 x	39.25" x 16" main shelf	6 x	small washers
		2 x	wing bolts with spring	6 x	small 10 mm hex nut
		2 x	metal rail	1 x	10 mm wrench
		2 x	hooked mounting bracket	1 x	Allen wrench, large

LIMITED WARRANTY: RocknRoller Multi-Cart shelves carry a one-year warranty against defective material or workmanship on components. As with any equipment, normal maintenance is required. Caution should be used when moving any load with Multi-Carts or any other dolly.

Rail Adjustment


The support rails and mounting brackets will fit between the handles. The rails feature a slotted hole for adjustment. If needed, the width of the rails can be adjusted by loosening the bolts that secure the rails to the bottom. Please make sure all of the bolts are tightened again before using the shelf.



Customer Service & Technical Support ACE PRODUCTS GROUP 3920 Cypress Drive, Suite B Petaluma, CA 94954 • 800-950-1095 • 707-765-1500 • www.rocknrollercart.com • info@aceproducts.com

Assembly Instructions

1. Install support tubes





With the RocknRoller Multi-Cart extended and both handles raised, install the round support tubes. Insert the 5/16" low profile socket head screws into the handle's predrilled holes from the outer edge, so the support tube in inside the handle. Make sure each tube is set to the same height before screwing them in securely.

2. In:

2. Install long rails

Install the 2 long metal rails to the 39" x 16" main shelf. Position the rails on the board so the hooked end sits just past the edge. Insert 6 small Allen bolts into the shelf from the textured side, and secure each with a washer and 10 mm hex nut. Do not tighten the bolts completely yet.

3. Secure shelf

Install the shelf by placing the hooked brackets on the support tubes. Align the deck pieces together and tighten all the short Allen bolts completely. The rails should now be secured to the shelf firmly.

There are also additional swivel tabs that may be installed by the shelf's hooks. They can be rotated under the support tubes once the deck is installed. This provides additional, light security and is optional.



Customer Service & Technical Support ACE PRODUCTS GROUP 3920 Cypress Drive, Suite B Petaluma, CA 94954 • 800-950-1095 • 707-765-1500 • www.rocknrollercart.com • info@aceproducts.com