

SAFETY DATA SHEET

RAPID DRY NAIL POLISH

ISSUE/ REVISION DATE: 05/01/2017

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/ UNDERTAKING

1.1 - IDENTIFICATION OF THE SUBSTANCE OR PREPARATION

PRODUCT N° : NAIL POLISH

PRODUCT/OTHER NAMES : COLOUR COSMETICS, NAIL LACQUER, NAIL VARNISH, BREATHABLE NAIL POLISH

1.2 - FINAL USE

Application of coloured nail polish to nails

1.3 - COMPANY IDENTIFICATION

Details of Supplier /Manufacturer

Company:	Oh Flossy Pty Ltd 637144355
Address:	Suite 2.16 / 75 Mary Street, St. Peters, Sydney Australia NSW 2044
Phone:	+614 7813 3129
Website:	www.ohflossy.com

Emergency Telephone Numbers:

Business Hours:	+614 7813 3129
After Hours :	+614 7813 3129
Poisons Information:	Australia: 131126 New Zealand: 0800764 766 or 0800 POISON

SECTION 2: HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE



GHS02; FLAMMABLE



GHS07 ; IRRITATING

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355

H225 : Highly Flammable liquid and vapour

Vapours form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. This material may produce a flammable vapour hazard.

1/7

2.2 LABEL ELEMENTS



RISK PHRASES

GHS02 Flammable



GHS07 Irritating

H225 Highly flammable liquid and vapour
H319 Cause serious eye irritation
H336 May cause drowsiness and dizziness

PRECAUTIONARY STATEMENTS

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking
P243 Take precautionary measures against static discharge
P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

2.3 OTHER HAZARDS

The mixture contains no substance conforming to the PBT/vPvB criteria of REACH Regulation.

SECTION 3: COMPOSITION/INFORMATIONS ON INGREDIENTS

3.2 MIXTURE

CHEMICAL CHARACTERIZATION CHEMICAL CHARACTERIZATION
Nitrocellulose with nitrogen content < 12.2 % and at a concentration < 20 % in a blend of solvents.

HAZARDOUS COMPONENTS

INGREDIENT	HAZARD SYMBOL (CE) No 1272/2008	CONCENTRATION	REGISTRATION NUMBER
ETHYL ACETATE CAS : 141 -78-6	FLAM. LIQ. 2 H225 EYE IRRIT. 2 H319 ACUTE TOX. 3 H336	20.0 – 30.0 %	01-2119475103-46-XXXX
BUTYL ACETATE CAS : 123-86-4	FLAM. LIQ. 3 H226 ACUTE TOX. 3 H336	19.0 - 25.0 %	01-2119485493-29-XXXX
NITROCELLULOSE CAS : 9004-70-0	FLAM. SOL. 1 H228	17.0 – 21.0 %	Polymer
ISOPROPYL ALCOHOL CAS : 67-63-0	FLAM LIQ. 2 H225 EYE IRRIT. 2 H319 STOT SE 3 H336	7.5 – 8.5 %	01-2119457558-25-XXXX

ADDITIONAL INFORMATION

For the wording of the listed risk phrases refer to section 16.

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355

SECTION 4: FIRST AID MEASURES

4.1 - DESCRIPTION OF FIRST AID MEASURES

SKIN CONTACT: Remove contaminated clothing and wash before reuse. Remove and destroy contaminated shoes. Flush with plenty of water.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.

INGESTION: Get medical attention **IMMEDIATELY**.

EYE CONTACT: Immediately wash the eyes with plenty of water for at least 10 min holding the eye open. Obtain medical attention urgently.

4.2 - MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED EFFECTS OF OVEREXPOSURE

Cause eye irritation. Harmful if swallowed. May cause nose and throat irritation. Causes skin irritation. May affect the brain or nervous system, causing dizziness, headache or nausea. Harmful if inhaled.

OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE

Narcosis, conjunctivitis, loss of coordination, vomiting, lacrimation, redness and swelling of eyes, difficulty with speech, reduced visibility, abdominal pain, swelling and redness of skin, fatigue, cough, dermatitis, drowsiness, unconsciousness.

PRIMARY ROUTE(S) OF ENTRY

Inhalation, skin contact, eyes.

MEDICAL CONDITIONS THAT CAN BE AGGRAVATED : NA

CHRONIC HEALTH HAZARDS

REPEATED OVEREXPOSURE TO THIS PRODUCT MAY CAUSE

Lung damage, liver abnormalities, kidney damage, central nervous system damage, blood effects.

In accordance with 29CFR1910.1200, this product contains no ingredients listed by NTP, IARC or OSHA as carcinogenic.

NOTICE

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

4.3 - IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No further relevant information available

SECTION 5: FIREFIGHTING MEASURES

5.1 - EXTINGUISHING MEDIA

Foam, Carbon Dioxide or Dry Chemical.

5.2 - SPECIAL FIREFIGHTING PROCEDURES

Water may be ineffective in fighting fire. If water is used to cool closed containers to prevent pressure build-up, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus is needed to protect fire-fighters from exposure to coating's hazardous ingredients and hazardous decomposition products.

5.3 - FOR FIREFIGHTERS

During emergency conditions, overexposure to decomposition products may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 - PERSONAL PRECAUTIONS

Avoid contact with the skin and the eyes. Keep away from heat and sources of ignition. Provide adequate ventilation.

6.2 - ENVIRONMENTAL PRECAUTIONS

Prevent further leakage or spillage. Do not discharge into the drains/surface waters/groundwater.

6.3 - METHODS FOR CLEANING UP

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations.

6.4 - ADDITIONAL INFORMATION

Consult trained personnel. Consider the information for "Personal Protection" in chapter 8 of this Safety Data Sheet.

SECTION 7: HANDLING AND STORAGE

7.1 - PRECAUTIONS FOR SAFE HANDLING

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

7.2 - PRECAUTIONS FOR SAFE STORAGE

Store in well-ventilated area. Keep containers (solvent resistant) closed when not in use. Store away from ignition sources. All equipment should be grounded. Avoid strong oxidizing agents, store in a clean, dry area.

7.3 - OTHER PRECAUTIONS

All precautions must be observed. Empty container may retain product residues (vapour or liquid).

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 - EXPOSURE LIMITS

COMPOSANT	CAS N°	DESC.	VALEUR	UNITE	COMMENTAIRES
BUTYL ACETATE <Acetic acid, Butyl Ester>	123-86-4	Press de Vap	15.0	mm/Hg	25°C
		Press de Vap	45.0	mm/Hg	50°C
		PEL -TWA	150.0	ppm ppm	
		TLV -STEL	200.0	ppm	15 Minutes
		PEL -STEL	200.0		15 Minutes
ETHYL ACETATE	141-78-6	Press de Vap	100.00	mm/Hg	27 °C
		Press de Vap	200.00	mm/Hg	42°C
		PEL -TWA	400.0	ppm	
ISOPROPANOL <ISOPROPYL ALCOHOL>	67-63-0	Press de Vap	40.0	mm/Hg	23.8°C
		Press de Vap	100.0	mm/Hg	39.5°C
		PEL -TWA	400.0	ppm ppm	
		TLV -STEL	500.0	ppm	15 Minutes 15
		PEL -STEL	500.0		Minutes

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355

8.2 - PERSONAL PROTECTION

RESPIRATORY PROTECTION

Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during application and handling unless air monitoring demonstrates vapour/mist levels below applicable limits. Follow respirator manufacturer's recommendations for selection and use.

VENTILATION

Sufficient ventilation must be provided to maintain airborne concentrations below TLV, PEL and LEL Limits as listed in Section 8.

PROTECTIVE GLOVES

Chemical resistant protective gloves (such as Neoprene or Butyle rubber) should be worn when handling this product. Check with glove manufacturer to determine proper glove type.

EYE PROTECTION

Splash -proof chemical goggles should be worn.

OTHER PROTECTIVE EQUIPMENT

Impervious clothing and boots should be worn. Eye bath and safety shower should be provided.

HYGENIC PRACTICES

Good personal hygiene practices are required at all times when handling chemicals. These practices include, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks and especially if contamination occurs.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

FORM	: Viscous liquid	
COLOUR	: Red	
ODOUR	: Fruity (Esters)	
OLFACTIVE THRESHOLD	: 50 ppm (Ethyl Acetate)	
MELTING POINT	: - 84 °C (Ethyl Acetate)	
BOILING POINT	: 77°C at 1013 hPa (Ethyl Acetate)	
BOILING RANGE	: 77 to 130°C	
SPECIFIC GRAVITY	: 0.980 - 1.020	
VAPOUR PRESSURE (hPa)	: 100 (20°C) (Ethyl Acetate)	
VAPOUR DENSITY (Relative : Air = 1)	: 3.04 (Ethyl Acetate)	
FLASH POINT	: - 5 °C	
AUTO IGNITION TEMPERATURE	: 460 °C	
FLAMMABLE LIMITS (% v/v)	: <u>Upper</u>	<u>Lower</u>
Ethyl Acetate	11.0	2.2
Butyl Acetate	7.6	1.7
Isopropanol	12.0	1.8
pH	: Not applicable	

SOLUBILITY IN WATER

: Insoluble

WATER/OCTANOL DISTRIBUTION COEFFICIENT

: Log Kow = 0.6 0 (Ethyl Acetate)

EVAPORATION RATE

: Slower than ether

VISCOSITY (Brookfield)

: 1500 - 4000 mPa.s

SECTION 10: STABILITY AND REACTIVITY

10.1 - REACTIVITY

Material is STABLE under non-emergency conditions.

10.2 - CHEMICAL STABILITY

Material WILL NOT undergo hazardous polymerization.

10.3 - HAZARDOUS REACTION Not known.

10.4 - CONDITIONS TO AVOID

Heat, sparks, open flame.

10.5 - MATERIALS TO AVOID

Sodium hydroxide, nitric acid, oxidizers, acids, alkali, metal, amines.

10.6 - HAZARDOUS DECOMPOSITION PRODUCTS

Methane, oxides of nitrogen. Carboxylic acids, various hydrocarbons, oxides of carbon, aldehydes, hydrogen cyanide, acids.

SECTION 11: TOXICOLOGICAL INFORMATIONS

INGREDIENT	LD50 (Oral, Rat)	LC50 (Inhal, Rat)	LC50 (Dermal, Rabbit)
BUTYL ACETATE	14000 mg/Kg	2000 ppm	
ETHYL ACETATE	11300 mg/Kg	1600 ppm (8h)	
ISOPROPYL ALCOHOL	5840 mg/Kg	16000 ppm (8h)	13000 mg/Kg

The product has not been tested. The statements on toxicology have been derived from the literature.

INGESTION

Important ingestion can cause nausea and a great narcosis with weakness, drowsiness and loss of consciousness.

INHALATION

Can cause irritation of the nose and the throat. At high concentration can cause narcosis.

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355

CONTACT WITH THE SKIN

Prolonged contact can cause crack in skin.

CONTACT WITH THE EYES

Can cause irritation of the conjunctive. Can cause injury of the cornea.

SECTION 12: ECOTOXICOLOGICAL INFORMATIONS

Any reject of this product in the sewer or stream must be avoided.

WATER HAZARD CLASS

WGK1: Slightly hazardous for water .

SECTION 13: DISPOSAL CONSIDERATIONS

Incinerate in a furnace where permitted under national and local regulations.

SECTION 14: TRANSPORT INFORMATIONS

ROAD TRANSPORT

Technical name : PAINT
ADR Class : 3
ADR Pack group : II
Tunnels Restriction Code : D/E
Danger label : 3
Kemler number : 33
UN Number : 1263
Hazchem Code : 3YE

IATA

Technical name : PAINT
UN Number : 1263
IATA Class : 3
Danger label : 3
Pack Group : II
Packing instr : 353(Passenger) – Maximum Quantity 5l
364(Cargo) – Maximum Quantity 60l
UN Number : ID 8000 CONSUMER COMMODITY

MARITIME TRANSPORT

Technical name : PAINT
UN Number : 1263
IMDG Class : 3
Marine pollutant : No
Ems Number : F-E, S-D
IMDG Pack Group : II

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355

Danger label : 3

Flash point : -5°C

Other indications relative to maritime transport:

-Not viscous product as per IMDG code 2.3.2.5

-Limited Quantity: 5l/30kg (gross)

-Certified packaging: Internal packaging metal, glass, plastic

External packaging: Carton 4G

SECTION 15: REGULATORY INFORMATIONS

No other data.

SECTION 16: OTHER INFORMATIONS

Relevant Phrases

H225 Highly flammable liquid and vapour

H226 Flammable liquid and vapour

H228 Flammable solid

H319 Cause serious eye irritation

H336 May cause drowsiness and dizziness

Oh Flossy Pty Ltd is committed to supplying safe products to our consumers and we continue to ensure the safety of our products and our active promotion of responsibility and concern for customer safety across all aspects of our business. This product has been tested and it conforms to our high quality standards. The information contained in this Safety Data Sheet is obtained from current and reliable sources. Oh Flossy Pty Ltd provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This Safety Data Sheet summarises our best current knowledge of the health and safety hazard information of the product, but does not claim to be all inclusive. This document is thus, intended only as a guide to the appropriate precautionary handling of the material. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Oh Flossy Pty Ltd assumes no responsibility for injury caused by abnormal or improper use of this product.

Oh Flossy PTY LTD Suite 2.16, 75 Mary St, St Peters, Sydney, NSW 2044 Australia

T 0478133129 www.ohflossy.com hello@ohflossy.com A.C.N 637 144 355