

Wrapped in Love Bracelet

Project B5002

Designer: Tracy Gonzales

This edgy wrap bracelet features TierraCast eyelets and findings with synthetic rubber cord, which is a fantastic alternative to leather and gives a similar look.

What You'll Need

Synthetic Rubber Cord, Flat 10x1.9mm, 1 Meter, Black

SKU: XCR-8006

Project uses 24 inches



TierraCast Antiqued Lead-Free Pewter Tribuckle Connector Clasp 1/2 Inch - 1 Piece

SKU: FCL-9381

Project uses 1 piece



TierraCast Fine Silver Plated Pewter Winged Heart Charm 17.5mm (1)

SKU: PND-5341

Project uses 1 piece



TierraCast Black Finish Brass Micro Washer For Jewelry 6mm - 10 Pieces

SKU: PND-12001

Project uses 2 pieces



TierraCast Silver Plated Brass Hollow Eyelets 3.8mm Diameter, 7mm Long - Pack of 10

SKU: FCO-4805

Project uses 1 piece



TierraCast Silver Plated Brass Hollow Eyelets 3.7mm Diameter, 5.2mm Long - Pack of 10

SKU: FCO-4799

Project uses 10 pieces



TierraCast Fine Silver Plated Brass Open Jump Rings 7.7mm 16 Gauge (25)

SKU: FJR-5415

Project uses 2 pieces



Silver Plated Head Pins 2 Inches/21 Gauge (X50)

SKU: FHP-5325

Project uses 1 piece



Czech Glass Round Party Beads 10mm - Dark Red (1 Strand / 18 Beads)

SKU: BCP-21004

Project uses 1 piece



Recommended Tools:

[XTL-5511] Beadsmith Jeweller's Micro Pliers Chain Nose Flat Nose, [XTL-5514] Beadsmith

Jewelry Fine Round Nose Micro Pliers, [XTL-5600] Xuron Sharp Flush Cutter Pliers -

Wire/Soft Flex, [XTL-0785] TierraCast Eyelet Setter And Anvil Tool - 1 Tool, [XTL-5502]

BeadSmith Rotating Leather Hole Punch Tool - Creates 6 Hole Sizes!, [XTL-5500] Cord Cutter
Tool For Regaliz Cord 3 Inches Long, [XTL-0248] Eurotool Brass Mallet For Metal Smithing - 1
Pound

Instructions

This wrap bracelet is approximately seven inches around (each wrap). To adjust the finished size of your bracelet, multiply the amount to increase or decrease by three and adjust the length of the cord accordingly.

1. You can see this bracelet made start to finish in the video How to Make the Wrapped in Love Bracelet.
2. Cut a length of synthetic rubber cord that is 24" long.
3. Thread the end of the cord through the smallest opening on the Tribuckle (ridge side up) and fold over the last 3/4".
4. Set the hole punch for a 2mm hole. Use the punch to make a hole through both folded layers of cord about 1/2" from the folded edge.
5. Thread a washer onto one of the longer eyelets and then insert the washer through the holes from the top. Thread a second washer onto the back of the eyelet.
6. Place the assembly flange side down onto the anvil, set eyelet setter into the tube, and tap gently with a hammer while rotating the setter at a slight angle until the eyelet is set.
7. Use a pencil to mark the placement for your 10 eyelets, about 2" apart along the bracelet, leaving the final 3" blank.
8. Set your hole punch for 2mm holes and punch a hole at each pencil mark.
9. Insert one of the shorter eyelets into one of the holes and set as before. Repeat with the remaining shorter eyelets to set all ten.
10. Thread your red bead onto a head pin and create a simple wire loop.
11. Open a jump ring and place the wire loop onto it. Thread it through the bottom opening of the Tribuckle and close the ring. Repeat this process to hang the winged heart charm next to the bead dangle.