


# Section 1

## Gas Hoses, Fittings & Valves



# Gas Hoses

## COOKERFLEX™ Natural Gas Hoses

Approved to BS669 Part 1, Manufactured in the UK

Incorporates a patented firesafe fusible plug which will shut off the gas supply at the socket in the event of a fire. For natural gas only.



KM637746

MANUFACTURED IN THE UK  
**COOKERFLEX**  
THE PROFESSIONAL DOMESTIC GAS HOSE



### Bayonet

Code	Size
THN120	2ft
THN130	3ft
THN140	4ft
THN150	5ft
THN160	6ft



### Micropoint

Code	Size
THN630	3ft
THN635	3ft 6"
THN640	4ft



### Nut & Union

Code	Size
THN320	2ft
THN330	3ft
THN340	4ft
THN350	5ft
THN360	6ft



### Angled Bayonet

Code	Size
THN220	2ft
THN230	3ft
THN240	4ft

## COOKERFLEX™ EN14800 Gas Hoses

Kitemark Approved

Manufactured using a stainless steel hose construction and kitemark approved by BSI to BS EN 14800.

Incorporates a patented firesafe fusible plug which will shut off the gas supply at the socket in the event of a fire.

Suitable for 1st, 2nd and 3rd family gases. Must be installed in accordance with BS6172 Installation Standard.



KM641091



### Bayonet

Code	Size
THUS1000	1m
THUS1250	1.25m
THUS1500	1.5m



### Micropoint

Code	Size
THUM1000	1m
THUM1250	1.25m
THUM1500	1.5m

### Angled Bayonet

Code	Size
THUA1000	1m
THUA1250	1.25m

## Catering Hoses

Approved to BS669 Part 2



Code	Size
CHC-12-1000	1/2" x 1m
CHC-12-1500	1/2" x 1.5m
CHC-34-1000	3/4" x 1m
CHC-34-1500	3/4" x 1.5m

Catering Hoses must have a yellow outer for hygiene and corrosion resistance purpose in accordance with BS669-2:1997.

Suitable for 1st, 2nd and 3rd family gases.

## Hobflex

Gas hob connecting hose

Code	Size / Description
HFLEX	1/2" x 15mm x 1m
HFLEX+	1/2" x 15mm x 1m (includes test point ball valve)

- Saves time & allows ease of installation for gas hobs
- Can be cut to length
- EN15266 semi-rigid pipe
- Kitemark approved
- DN15 x 15mm connector
- Includes self amalgamating tape



KM646363



# Gas Hose Accessories

## Cooker Sockets

- For use with natural gas and LPG
- Kitemark approved
- CE marked
- EN15069



### Straight Bayonet

Code	Size
B593	1/2"



### Angled Bayonet

Code	Size
B553	1/2"



### Micropoint Socket

Code	Size
B614	1/2"

## Cooker Safety

As required by BS6172 installation standard.



### Stability Chain & Hook

Code	Description
GCSC	Stability chain kit
GCRC	1m chain
GCRHOOK	1m chain & hook

As required by BS6172 installation standard.



### Stability Brackets

Code	Description
CSB	Cooker stability bracket

## Wall Connectors



### Straight Wall Plate Connector

Code	Size
REWCS	15mm x 1/2"



### Angled Wall Plate Connector

Code	Size
REWCA	15mm x 1/2"



### Straight Connector with stub

Code	Size
B579	15mm x 1/2"




### Strapped elbow

Code	Size
B580	15mm x 1/2"

# Isolation Valves & Gascocks

## TESLA lever ball valves EN331

- Full bore
- Suitable for natural gas, LPG and oil
- Approved to BS EN331
- Nickel plated
- PN25

 Temperature range:  
-10°C to +110°C



### Compression

Code	Size
GB/BVL15	15mm
GB/BVL22	22mm
GB/BVL28	28mm
GB/BVL35	35mm
GB/BVL 42	42mm
GB/BVL54	54mm

## Rigid fan gascocks

Traditional style with fan key format.



### Compression

Code	Size
TGC020	15mm
TGC025	22mm



### Capillary

Code	Size
TGC160	15mm
TGC165	22mm


## Drop fan gascocks



### 15mm Capillary Union

Code	Size
TGC020	15mm

- Compression to BS EN1254-2
- CE marked
- 1/4 turn
- Threads to ISO 228 (formerly BS 21)
- Yellow handle

 Temperature range:  
-20°C to +130°C



### Female BSP

Code	Size
GB/BVL14	1/4"
GB/BVL38	3/8"
GB/BVL12	1/2"
GB/BVL34	3/4"
GB/BVL1	1"
GB/BVL114	1.1/4"
GB/BVL112	1.1/2"
GB/BVL2	2"

## Test point valves

- Full bore
- 1/4 turn
- CE marked



- EN331 approved
- Includes low pressure test point

### Lever operated

Code	Size
GT/BVL34	3/4"
GT/BVL1	1"



### Screwdriver operated

Code	Size
GTBV15	15mm
GTBV22	22mm


## Test Point Nipple





Code	Size
GTN18	1/8"

## 'T' handle ball valves

- Full bore
- Suitable for natural gas, LPG and oil
- Approved to BS EN331
- Nickel plated
- PN25

 Temperature range:  
-20°C to +130°C



 Temperature range:  
-10°C to +110°C

### 'T' handle

Code	Size
GB/BVT14	1/4"
GB/BVT12	1/2"
GB/BVT34	3/4"
GB/BVT15	15mm
GB/BVT22	22mm
GB/BVT28	28mm



See page 33 for WRAS approved ballvalves

## Gas Isolation Valves

- EN331 approved
- CE Marked
- Ends to EN1254



### ISOGAS

Code	Size
GC802	8mm
GC102	10mm
GC1502	15mm
GC2202	22mm

# Mini Ball Valves - EN331

- Suitable for natural gas, LPG and oil
- Approved to BS EN331
- Yellow inserts included
- Compression ends to BS EN1254
- Suitable for class CS and D fuel oils to BS2869 (excluding petrol)
- CE marked



## Compression

Code	Size
GCM08	8mm
GCM10	10mm
GCM12	12mm
GCM15	15mm



## Compression reducing

Code	Size
GCM1008	10mm x 8mm
GCM1508	15mm x 8mm
GCM1510	15mm x 10mm
GCM1512	15mm x 12mm



## Angled compression

Code	Size
GCM08A	8mm
GCM10A	10mm
GCM15A	15mm

## Angled reducing compression

Code	Size
GCM1508A	15mm x 8mm
GCM1510A	15mm x 10mm



## Female

Code	Size
GCM14	1/4"
GCM38	3/8"



## Male x Female

Code	Size
GCM14MF	1/4"
GCM38MF	3/8"



## BSPT Male x Compression

Code	Size
GCM0814	1/4" x 8mm
GCM1014	1/4" x 10mm
GCM1038	3/8" x 10mm
GCM1215M	1/2" x 15mm



## Integral backplate

Code	Size / Description
GCM08BP	8mm
GCM08BPR	8mm (red insert)
GCM10BP	10mm

# Gas Meter Fittings & Accessories

## Meter Unions

Manufactured in accordance with BS746:2014

Grooved, allowing fitment of meter brackets.  
Supplied with washer.



### 22mm Grooved

Code	Size
GMU221	22mm x 1"

### 22/28mm Grooved

Code	Size
GM078	22mm/28mm x 1"

Suitable for either 22mm or 28mm fitting. The 22mm bore allows the pipe to be fitted in the shank. The 28mm outside diameter allows use of a tube coupling.



### Standard

Code	Size
GM077	22mm/28mm x 1"



### Female Union x BSPT Male without Lug

Code	Size
GMU1	1" x 1"
GMU114	1 1/4" x 1.1/4"
GMU1-34	1" x 3/4"



### Female Union x Capillary with Lug

Code	Size
GMU1-22LUG	1" x 22mm

## Meter Accessories

### Sealing discs



Code	Size
B534	3/4"
B534/1	1"

### Meter caps



Code	Size
B535	3/4"
B535/1	1"

### Meter union washers



Code	Size
B353	3/4"
B351	1"
GM079	1.1/4"

### Meter cap/adaptor washers



Code	Size
B350	3/4"
B352	1"



### Gas Meter Connectors

Code	Size
GM-MC114/400	1.1/4" x 400mm
GM-MC34/390	3/4" x 390mm



### Gas meter box key

Code
GMK

# Restrictor Tubes & Accessories

## Restrictor Tubes



### 1m Long, 1/4" BSPT Thread

Code	Size	Finish
RTC18	8mm	Chrome
RTBR18	8mm	Brass

### 1.25m Long, 1/4" BSPT Thread

Code	Size	Finish
RTC1258	8mm	Chrome

## Restrictor Kit with Restrictor Tube

Kit includes:  
1" x 8mm restrictor elbow, floorplate, extension piece, 2 crush rings, 15mm x 1/4" brass adaptor & 1m x 8mm restrictor tube.



Code	Size	Finish
GK48TA	8mm	Chrome

## Restrictor Elbows



### 1" Tall

Code	Size	Finish
RE18	8mm	Chrome

### 2" Tall

Code	Size	Finish
RE28	8mm	Chrome

## Restrictor Kits

Kit includes:  
1" x 8mm restrictor elbow, floorplate, extension piece & 2 crush rings.



### 4" Extension

Code	Size	Finish
GK48	8mm	Chrome
GK48PB	8mm	Polished Brass

## Floorplates

A restrictor elbow may be screwed directly to the floorplate, or can be used with the extension pieces to give extra height.



### 1/4" Male BSPT x Female BSP

Code	Finish
RF18	Chrome

## Restrictor Adaptors



### 15mm x 1/4"

Code	Finish
GA15	Brass
GA15CP	Chrome

## Gland Nuts



Code	Description
REGN08	8mm chrome
REGN12	12mm chrome

## Extension Pieces

Can be fitted between the restrictor elbow and floorplate to give extra height. The exposed threads may be hidden by using the collapsible crush rings.



### 1/4" Male BSPT x Female BSP

Code	Finish
EXCP	Chrome

## Backnee Elbows

Brass elbows which may be used to pass the gas supply to the bottom of the floor plate. eg. The long arm can be used through floorboards. 65 x 65mm overall length each side.



### 15mm x 1/4" BSPP Male/Female

Code	A Size	B Size	Finish
RE1514	15mm	1/4"	Brass


## Crush Rings



Code	Finish
CCR	Chrome

## Gas Fire Backplates

Closure plates for gas fires.



Code	Size	Finish
AB2418	24" x 18"	Aluminium
AB36	36" x 36"	Aluminium

# Corrugated Stainless Steel Tubing

## A safe main line connection for all domestic gas appliances

A lightweight semi-rigid corrugated stainless steel tube and fittings system (CSST) that is a time saving, cost effective alternative to rigid pipework for the supply of natural and liquefied gases (LPG) in domestic buildings.

Manufactured and approved to the European Standard EN15266:2007, referring to 'Stainless Steel pliable corrugated tubing kits in buildings for gas with an operating pressure up to 0.5bar'. The aim of the Standard (EN 15266) is to improve the safety level of domestic natural gas connections in the building and to provide countless benefits for both users and installers.

This system prevents heavy lifting, extensive measuring, cutting and threading with connections completed with simple hand tools safely and quickly.

### Features & Benefits

- Typically requires fewer fittings per installation than conventional rigid pipework, saving time and money
- Flexible piping system
- Connections can be made with simple hand tools, safely and quickly
- Connects to existing gas lines
- Flame free installation. No torch, no gas, no flux, no system contaminants
- Competitive and stable price basis

Kitemark pending



## 2 YEAR WARRANTY

### Starter Kits

Our starter kits contain everything you need to get up and running, use along with the instructions to ensure a perfect installation every time!

Code	Size
TFX1210KIT	DN12
TFX3410KIT	DN15
TFX0110KIT	DN20
TFX11410KIT	DN25

#### What's included

- 10 metre coil of pipe
- 2 x male adaptors
- 1 x roll of self amalgamating tape



### Tubing



Code	Size	Length	Weight (kg)
TIF1210	DN12	10m	3
TIF1230	DN12	30m	6
TIF1275	DN12	75m	19
TIF3410	DN15	10m	3
TIF3430	DN15	30m	7
TIF3475	DN15	75m	20
TIF0110	DN20	10m	3.5
TIF0130	DN20	30m	9
TIF0175	DN20	75m	33
TIF11410	DN25	10m	4
TIF11430	DN25	30m	12
TIF11475	DN25	75m	35
TIF11210	DN32	10m	
TIF11230	DN32	30m	
TIF11275	DN32	75m	

Note: 75m lengths supplied on bobbins

### Split Rings



Code	Size
TFXSR12	DN12
TFXSR15	DN15
TFXSR20	DN20
TFXSR25	DN25

### Male Adaptor



Code	Size
TFXM1212	DN12 x 1/2"
TFXM1512	DN15 x 1/2"
TFXM2034	DN20 x 3/4"
TFXM251	DN25 x 1"
TFXM32114	DN32 x 1.1/4"

### Female Adaptor



Code	Size
TFXF1212	DN12 x 1/2"
TFXF1512	DN15 x 1/2"
TFXF2034	DN20 x 3/4"
TFXF251	DN25 x 1"
TFXF32114	DN32 x 1.1/4"

### Couplers



Code	Size
TFXC12	DN12
TFXC15	DN15
TFXC20	DN20
TFXC25	DN25

### Adaptor



Code	Size
TFX1215C	DN12 x 15mm
TFX1515C	DN15 x 15mm
TFX1522C	DN15 x 22mm
TFX2022C	DN20 x 22mm
TFX2522C	DN25 x 22mm

### Tees



Code	A	B	C
TFXT201515	DN20	DN15	DN15
TFXT201520	DN20	DN15	DN20
TFXT20	DN20	DN20	DN20
TFXT252020	DN25	DN20	DN20
TFXT252520	DN25	DN25	DN20
TFXT25	DN25	DN25	DN25

### Tape

- Self amalgamating
- Protects the exposed hose against corrosion



Code	Size
TIFTAPE	25mm x 3m