

RUST-OLEUM®
— INDUSTRIAL —



ULTRA CLEANABLE MATT



Optimally cleanable, extra matt wall paint

- Remains matt after cleaning
- No white marking
- Optimally cleanable
- Extra matt
- Scrub-resistant, Class 1

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

ULTRA CLEANABLE MATT

DESCRIPTION

Optimally cleanable, extra matt wall paint based on a special binding agent combination. The dry paint coating is moisture-repellent to reduce dirt build-up and remains permanently matt after cleaning. Highly suitable for use on walls in public buildings and rooms that are prone to dirt/dust accumulation such as kitchens, bathrooms and entrance halls. For interior use.

RECOMMENDED USE

As a durable and very easily cleanable, even matt finish for interior walls and ceilings. Suitable surfaces include: existing coats of wall paint, cement and plasterwork, concrete, brick, gypsum panelling, etc. Also extremely suitable for painting glass fibre fabric.

RECOMMENDED SYSTEM

General information: The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Repair cracks and fissures. Remove and/or repair all loose and unstable coats.

New, untreated substrates

- Prime highly absorbent surfaces in their entirety using Stabilising primer.
- Thoroughly clean powdery surfaces. Prime with Stabilising primer after allowing to dry.
- After drying, apply 2 coats of Ultra Clean.

Existing intact coats of wall paint

- Clean using Paint cleaner.
- Apply an intermediate coat of Wall Primer Extra Opaque if necessary.
- After drying, apply 2 coats of Ultra Clean.

Existing, flaking coats of wall paint

- Remove loose parts.
- Thoroughly wash powdery coats and allow them to dry.
- Carry out any repairs.
- Prime with Stabilising primer.
- After drying, apply 2 coats of Ultra Clean.

Contamination caused by nicotine, damp, rust or soot

- Clean thoroughly using Paint cleaner.
- Treat surface/stain with Sealing primer.
- After drying, apply 2 coats of Ultra Clean.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact Rust-Oleum Europe.

TECHNICAL DATA

Density:	1.50
Gloss Level:	Matt
Gloss level at 85°:	1%
Solids content in volume:	43%

DRYING TIMES AT 20°C/RH 50%

Touch dry:	2 h
Dry to recoat:	6 h

RECOMMENDED WET FILM THICKNESS

123 µ

RECOMMENDED DRY FILM THICKNESS

53 µ

THEORETICAL CONSUMPTION

Approx. 8 m²/litre per coat

PRACTICAL CONSUMPTION

The actual coverage depends on the nature and the structure of the surface and the application method.

SURFACE PREPARATION

The surface must be capable of supporting the paint, completely set, clean, dry, and free from dust or grease. Repair cracks and fissures. Remove and/or repair all loose and unstable coats.

DIRECTIONS FOR USE

Stir thoroughly prior to use. The first coat can be diluted with a maximum of 5% water. Apply in 1 or 2 coats using a suitable brush, paint roller or paint sprayer. For optimal cleanability, apply 2 coats. To avoid visible marks, always work wet-on-wet and distribute the paint evenly. Back-roll all overlaps in the same direction. Do not touch up when drying. Very easy to touch up after drying.

APPLICATION CONDITIONS

not use at temperatures below +8°C. Only use when the surface temperature is at least 3°C above the dew point temperature. Always use the required personal protective equipment when applying this product. Do not inhale spray mist/fumes given off by products. Always ventilate appropriately when applying.

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 0.017-0.021"

Pressure: approx. 180 bars

The stated settings for spraying this product are indicative and should be taken as your starting point. Depending on the on-site conditions, the settings will have to be determined by the person applying the paint.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Nozzle: 0.015-0.019"

Pressure: approx. 125 bars

Air pressure: approx. 1.5 bars

Dilute: no

The stated settings for spraying this product are indicative and should be taken as your starting point. Depending on the on-site conditions, the settings will have to be determined by the person applying the paint.

CLEANING OF EQUIPMENT / SPILLS

Water

SAFETY DATA

VOC level:	30 g/l
VOC category:	A/a
VOC limit:	30 g/l
Flashpoint:	Not flammable
Remarks regarding safety:	Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.

SHELF LIFE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Date issued: 20/06/2019

Available colours & pack sizes : Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer : The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu