4D-16 (TC) RE HEPA MR (ASBESTOS)

Remediation of wet/saturated Asbestos - Dual Motors





Applicable Requirements : ANSI/UL 1017 CSA C22.2 No.243



Characteristics







- HEPA Filter Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST-RP-CC001, H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- For general housekeeping
- Dual Bypass/Dual Speed Heavy Duty motors. 2000 watts (2400 maximum)
- Middle Ring for Polyliner, for the recovery of wet/saturated asbestos.
- For wet and dry recovery
- Polyethylene recovery tank.
- Silent operation
- Mounted on a Tilting Cart (TC) for easy disposal of recovered materials.

Specifications

4D-16 (TC) RE HEPA MR (ASBESTOS)	110569A
Model Name	4D-16 (TC) RE HEPA MR (ASBESTOS)
Type (Powerhead)	Electric
Voltage	115 V
Hertz	60 Hz
Phase	Single
Wattage	1955 W
Power	2.6 HP
Amperage	17 amps.
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ 0
Plug Type	Not Included
Suction Inlet	2 "
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Dry Recovery - Tank	15 Gal
Wet Recovery Capacity	15 Gal
Length	27 "
Width	27 "
Weight (Vacuum Only)	101 lbs.
Height	46 "
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Main Cloth Filter - Included



Dralon Pre-Filter & Liquid Filter - Included



Asbestos Polyliner (6) W retaining clip (not shown) - Included



PVC Crushproof Suction Hose Assembly - Included



Conical Nozzle and Adaptor - Included