



DUST IGNITION PROTECTED
Division 2, Class II, Groups F and G

ESD Safe Vacuum Cleaners for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Characteristics



HEPA - Included



High Efficiency



Detachable Tank



Dry Recovery



Dual Motor



Static Dissipating



SS 430



SD Accessories -
Included



- Intermittent Housekeeping and General Cleaning.
- Dual Bypass/Dual Speed Ametek® long life motors
- Includes 5 HEPA filters. Class H14. Individually factory tested
- Manual Filter Shaker (MFS) with SD* Teflon Laminated Main Cloth Filter Assembly.
- Detachable Recovery Tank (DT) for easy disposal of recovered materials
- Material to be recovered within a conductive polyliner recovery bag for easy disposal
- Front mounted floor tool, 28" (71cm) is ideal for larger surfaces in hazardous locations/area - optional

Specifications

4D-35L EX DT MFS HEPA	113300A
Model Name	4D-35L EX DT MFS HEPA
Type (Powerhead)	Electric
Voltage	120 V
Hertz	60 Hz
Phase	Single
Wattage	2040 W
Power	2.7 HP
Amperage	15.2 amps.
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ O
Plug Type	20 Amps Explosion Proof
Suction Inlet	2 "
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dry Recovery - Tank	9.2 Gal
Length	28 "
Width	23.5 "
Weight (Vacuum Only)	117 lbs.
Height	54.5 "
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



4D-35LEX Suspended Powerhead



4D-35LEX DT MFS HEPA with Recovery Tank removed



4D-35LEX DT with optional Front Mounted Floor Brush (MRP version shown)



Ø2" (Ø50mm) Static Dissipative Tools and Accessories - Included



HEPA Filter - Included



Main Cloth Filter and Cage, Static Dissipative - Included



Conductive Polyliner Recovery Bag - Optional