



PHONE: 844-605-3266

WWW.DAMNINDUSTRIES.COM

DAMN INDUSTRIES, 2569 W PAWNEE, WICHITA KS 67213

# **RANGE BOSS**

SPECIFICATIONS AND TECHNICAL DATA

#### STANDARD FEATURES:

- · 2,000—3,500 CFM -DEPENDING ON OPTIONS SELECTED—CONSULT FAN
- **CURVES**
- · BELT DRIVEN-BLOWER
- SIDE LOAD, EASY FILTER ACCESS
- · FILTER CHANGE LIGHT OR MAGNAHELIC GAUGE
- · CAM-LOCK POSITIVE FILTER SEALING
- · FULL RANGE OF OPTIONS

#### **OPTIONS:**

- ·11/2 OR 3 HP MOTOR OPTIONS
- · WRAP-AROUND PREFILTER MOD-
- · 99.97% DOP HEPA FILTER
- $\cdot$  24" X 24" X 12" REFILLABLE MODULES–
- WITH UP TO 80 LBS OF CAR-BON
- · MULTIPLE PRE-FILTER OPTIONS · MULTIPLE FILTER OPTIONS
- OIL IMPINGER / OIL DRAIN KIT FOR MIST COLLECTION

- · MULTIPLE MOUNTING OPTIONS AVAILABLE
- · PULLEY OPTIONS FOR LOW,/MED./ HIGH STATIC APPLICA-TIONS
- · SOURCE CAPTURE MODULE WITH ONE, TWO OR THREE INLETS
- · MOTOR CONTROLS FOR 3-PHASE OPER-ATION
- · EXHAUST OPTIONS— STRAIGHT/ FRONT/REAR
- · SILENCER FOR STRAIGHT EXHAUST









#### **TYPICAL APPLICATIONS:**

- · AMBIENT DUST OR MIST CAPTURE
- · SOURCE CAPTURE PROCESS DUSTS & MISTS · WELDING SMOKE & FUMES
- · GRINDING / SANDING / POLISHING METALWORKING / COMPOSITES
- OTHER NUISANCE DUSTS GENERATED IN INDUSTRIAL PROCESSES

# **HOW IT WORKS:**

POLLUTED AIR FLOWS THROUGH A PLEATED OR FOAM PREFILTER, EFFECTIVELY REMOVING THE LARGER PARTICLES OF THE POLLUTANT.

NEXT THE AIR PASSES THROUGH THE MAIN FILTRATION SYSTEM. THIS PORTION CON-TAINS THE PRIMARY FILTER ME-DIA, A BAG FILTER, HEPA FIL-TER, CARBON MODULE OR A COMBINATION. THIS SYSTEM CAPTURES MINUTE PARTICLES OF AIRBORNE IMPURITIES AND ABSORBS GASES AND ODORS. THE DISCHARGED AIR IS THEN POLLUTION-FREE.

## **RB3510 SPECIFICATIONS:**

### **OVERALL DIMENSIONS:**

26" H X 26" W X 69.5" L NO SILENCER 26" H X 26" W X 93.5" L W / SILENCER

## WEIGHT:

268LBS ACTUAL WEIGHT \*300 LBS SHIPPING WEIGHT

WEIGHT VARIES DEPENDING UPON OPTIONS SELECTED

### CABINET:

HEAVY DUTY 16 GA. WELDED GALVANEAL STEEL W/EXTERIOR SURFACES GROUND SMOOTH

### FINISH:

INDUSTRIAL GRADE TEXTURED BAKED CHARCOAL ENAMEL PAINT—INSIDE AND OUT

### FILTRATION OPTIONS:

ONE EA. MERV 15, 24" X 24" X 32" 95% BAG FILTERS ONE EA. MERV 15, 24" X 24" X 32" 55% BAG FILTER ONE EA MERV 15, 24" 24" X 15" 55% BAG FILTER ONE EA MERV 15, 24" X 24" X 15" 95% BAG FILTER

REFILLABLE MODULE W/ CARBON (UP TO 80 LBS CARBON) 95% OR 99.97% DOP HEPA

### PREFILTER:

2" PLEATED PRE-FILTER
2" ALUMINUM MESH PRE-FILTER 2" BAFFLE IMPINGER
4" PLEATED PRE-FILTER
WRAP-AROUND DUO-CUBE PREFILTER

### FILTER ACCESS:

FRONT LOAD FOR EASY ACCESS SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

### FILTER ACCESS:

FRONT LOAD FOR EASY ACCESS

### **NOISE LEVEL:**

79 DBA @ 6' FROM EXHAUST

### INLET / EXHAUST:

STRAIGHT EXHAUST—INTAKE AT END / EXHAUST AT OPPOSITE END THROUGH 4 WAY ADJUSTABLE GRILLE

SIDE EXHAUST—INTAKE AT END / EXHAUST EITHER FRONT OR REAR

### MOTOR:

1 1/2 HP, 1740 RPM ,TEFC, SINGLE PH 3 HP, 208-230 / 460 V TEFC, 3 PH  $\,$ 

### **BLOWER:**

12-9 BELT DRIVEN

### INPUT VOLTAGE:

120V, SINGLE PH (1 1/2 HP ONLY) 230/460 VAC, 60 HZ, 3-PHASE ( 3 HP ONLY)

### MAX CURRENT:

1/1/2 HP, 120V—17.2 AMPS 3 HP, 230V / 460V—8.4 AMPS / 4.2 AMPS

### AIR FLOW:

UP TO 3,500 CFM—DEPENDENT ON OPTION CHOICES

# FILTER CHANGE INDICATOR (OPTIONAL):

FILTER CHANGE LIGHT







