

SWITLIK

OPR

Offshore Passage Raft




MADE IN USA
SELF-CERTIFIED



Scan this code for
more details about
the CPR Coastal
Passage Raft

For use in an offshore emergency.

Safety for everyone onboard your offshore excursion



The OPR Offshore Passage Raft is our modern and lightweight solution based off of decades of prior designs, research and testing. With plenty of freeboard for high seas and advanced features such as our convertible canopy system, heat sealed construction, and four rigid boarding steps, the OPR is the “real deal” in true offshore life rafts.

*For those who venture to farther waypoints, add our available Toroidal Stability Device (TSD) for the ultimate ballast system.

Specifications

Part Number: OPR-1330-series

Fiberglass Hard Case:

Weight: 71 lbs. (32.2 kg.) /75 lbs. with TSD
Dimensions: 31.5 in. L x 21.5 in. W x 13 in. H
Material: Hand Laid Fiberglass
Aluminum Cradle Material: AL 6463 T55
Case Color: White

Soft Valise Case:

Weight: 49 lbs. (22.7kg.) /55 lbs. with TSD
Dimensions: 24 in. L x 14 in. W x 12 in. H
Material: Nylon Cordura™
Case Color: Orange

Life Raft:

Buoyancy Tube Diameter: 9.75 in. (24.77 cm.)
Freeboard: 19.5 in. (49.53 cm.)
Inflated Raft Dimensions: 83.98 in. Width at flats (90.89 in. at corners)
Floor Area (Total): 24 sq. ft. (2.23 sq. m.)
Buoyancy in Fresh Water: Total: 1,324 lbs. (600.6 kg)
Buoyancy in Salt Water: Total: 1,358 lbs. (616 kg.)
Cylinder Charge Pressure: 3,000 p.s.i.
Operating Temperature Range: -22°F to +160°F
Inflation System: Air
Buoyancy Tube Fabric: Polyurethane Coated Nylon

Standard Features

- 2 Heat Sealed Buoyancy Chambers
- Painter/Static Line (length, 35 ft.)
- Lifelines (inner)
- Lifelines (outer)
- Reflective Patches
- Topping off/Pressure Relief Valve (2)
- 4 Boarding Steps w/ Reinforced Floating Ladders

Standard Equipment

- Water Activated Exterior Locator Light
- Sea Anchor (automatically deployed)
- Heaving Ring and Line
- Raft Use Instructions/Owner's Manual
- Floating Knife
- Waterproof Solar Powered Flashlight
- Manual Inflation Pump
- Repair Clamps (2 ea.)
- Inflatable Floor

Optional Equipment

- Anodized Aluminum Deck Mounting Cradle
- USCG Approved Hydrostatic Release
- Toroidal Stability Device



SWITLIK
SIGNATURES



Air Charge Inflation
System



Heat Sealed Technology



Convertible Canopy
System



Five Year Service Interval

Prices and Specifications Subject to Change Without Notice

SWITLIK SURVIVAL COMPANY

1325 East State Street Trenton, NJ 08609
Phone: 609-587-3300 Fax: 609-586-6647
E-Mail: info@switlik.com

WWW. **SWITLIK** .COM