
Automatic Adjustment Type Release Movement Alteration Kit Installation Manual

[JZA70 1JZ-GTE/MA70 7M-GTE]







Picture 1

Installation

- 1. Remove genuine release fork, release sleeve and linkage base.
- 2. D is connect T bracket and sleeve fork temporarily.
- 3. Fix the T bracket referring to the picture above.
- 4. Install the release fork set as the picture above.
- 5. Connect the release fork and T bracket again.
- 6. Install the sleeve set onto the front cover.

Caution: Check to see if the sleeve set is bose to its rotation. If it is stiff, please adjust the T bracket so that the sleeve set gets a little bose.

- 7. Bolt on the pivot base on to the transmission case.
 - Caution: If the bolts do not fit, please bosen the pivot and adjust the angle.

Then start all over from 4.

- 8. The configuration of the bell housing may differ depending on vehicle model and/or model year. If the parts interfere with the case, please file down or grind the bell housing.
- 9. Set enclosed push rod.
- 10. Rem ove genuine taper spring in the release cylinder cup and replace with enclosed taper spring.

General Warning

- X Check to see if all the parts are enclosed.
- X You must use all parts enclosed in the kit.
- X Please be aware of potential risks and hazards when installing our products. We do not take any responsibility for any loss and/or injury occurred when our products are modified, re-used and/or ill-fitted.
- Spray aerosol lubricant to the appropriate surface of the moving parts. Periodical lubrication is recommended.
- X The clutch release movement alteration parts are expendables. When excessive wear or damage is found, all concerning parts should be replaced at the same time.
- X All information on this sheet is based on Japanese Domestic Model vehicles and may not be applicable in your country.
- X Specification may be changed without notice.



464 OKIMOTO OKAYAMA-CITY OKAYAMA 702-8001 TEL(086)277-8609 FAX(086)277-8115

URL:www.osgiken.co.jp/