


# Supra Turbo Clutch Release Movement Alteration Kit Installation Manual Automatic Adjustment Type

## 【JZA80/2JZ-GTE w/6speed transmission】



### Enclosed Parts in the Kit

(Please Check all the Parts before Installation)

#### Name of the Parts

##### <Front Cover>

##### <Fork Set:Pre-assembled at Factory>

Release Fork Set

Sleeve Fork Set

Pivot Base (Pivot, Leaf Spring, Nut, Stopper Bolt)

T-Bracket (Guide Shaft, Guide Bushing, Circlip)

Pin, 2 Circlips for Pin, Sleeve Bearing, 2 Springs

##### <Others>

4 Bolts for Front Cover (M6x15L)

2 Bolts for Pivot Base (M8x15L)

2 Bolts for T-Bracket (M10x25L)

Taper Spring

Push Rod



### Installation

1. Remove genuine release fork, release sleeve, front cover and linkage base.
2. Set enclosed front cover with bolts.
3. Set the sleeve bearing to the front cover, while the fork set being on it. See the picture above as a reference.
4. Set the pivot base and T-Bracket with the bolts provided in this kit. Do not tighten them fully yet.  
At this point, see if the sleeve operates smoothly.  
If it does not operate smoothly, the T-Bracket is needed to be readjusted.
5. Check if all the moving parts operate smoothly. After that, tighten the bolts fully.
6. Screw and adjust stopper bolt with appropriate screw driver until it touches bell housing, then lock the bolt with provided nut.
7. Take the genuine release slave cylinder to pieces. Exchange the genuine spring with enclosed taper spring.
8. Replace genuine push rod assembly with enclosed push rod.

### General Warning

- ※TOYOTA 2JZ Clutch Release Movement Alteration Kit is developed from manual to automatic adjustment. (10, March, 2007)
- ※Check to see if all the parts are enclosed.
- ※ Please be aware of potential risks and hazards when installing our products. We do not take any responsibility for any loss and/or injury occurred when our products are modified, re-used and/or ill-fitted.
- ※Spray aerosol lubricant to the appropriate surface of the moving parts.  
Periodical lubrication is recommended.
- ※The clutch release movement alteration parts are expendables. When excessive wear or damage is found, all concerning parts should be replaced at the same time.
- ※All information on this sheet is based on Japanese Domestic Model vehicles and may not be applicable in your country.
- ※Specification may be changed without notice.

**OSGIKEN**  
Racing Power Unit &  
Parts Development

464 OKIMOTO OKAYAMA-CITY OKAYAMA 702-8001 TEL(086)277-8609 FAX(086)277-8115

URL:www.osgiken.co.jp/