

# Automatic Adjustment Type Release Movement Alteration Kit Installation Manual

## 【NSX NA1/C30A】

Chart 1



### Enclosed Items

#### Fork Set (Pre-assembled)

- Fork Dust Cover
- T-Bracket & Pin
- Sleeve Bearing

#### Cylinder Set (Pre-assembled)

- Cylinder
- Push Rod
- Push Rod Stay
- Fork Arm x 2
- Fork Connection Shaft
- L-Bracket

#### Bolts

- Bolt (M8 x 25L) for Cylinder x 2

Chart 2



### Installation

1. Remove genuine parts release fork, release sleeve, release cylinder, dust cover and pivot bracket.
2. Install sleeve bearing and fork on the front cover. (See Chart 1)
3. Install T-bracket using enclosed bolts. At this time, install fork dust cover. (See Chart 1)
4. Install cylinder on the bell housing with enclosed bolts. (See Chart 2)
5. Take apart the shaft of the fork connection part (See Chart 2) and connect the fork and fork arm. At this time, install washers outside the fork arm.
6. Install the hose to where the genuine hose was.

### General Warning

- ※Check to see if all the parts are enclosed.
- ※ Please be aware of potential risks and hazards when installing our products. We do not take any responsibility for any loss and/or injury occurred when our products are modified, re-used and/or ill-fitted.
- ※Spray aerosol lubricant to the appropriate surface of the moving parts.  
Periodical lubrication is recommended.
- ※The clutch release movement alteration parts are expendables. When excessive wear or damage is found, all concerning parts should be replaced at the same time.
- ※All information on this sheet is based on Japanese Domestic Model vehicles and may not be applicable in your country.

**OSGIKEN**

464 OKIMOTO OKAYAMA-CITY OKAYAMA 702-8001 TEL(086)277-6609 FAX(086)277-8115

URL:www.osgiken.co.jp/