

X TAPED HI VIS LIGHTWEIGHT DRILL RAIL COVERALL With Biomotion Taping

BC6316XT



Rail Orange
(BVOR)



Features

- Reflective taped H pattern around body with X back and biomotion taping on sleeves and legs
- Australian Rail compliant
- Nylon press stud front and sleeve cuff closure
- Chest pocket with zippered opening on right hand side
- Chest pocket with tool division on left hand side
- Two angled side pockets with openings to body
- Back patch pocket and ruler pocket on right hand side
- Mobile phone pocket on right hand side
- Double layered knee for durability

Fabric

100% Cotton Preshrunk Drill 190gsm

Size

- 77 - 117R
- 92 - 132S



AUSTRALIAN & INTERNATIONAL STANDARDS

Australian/ New Zealand Standards

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
BISLEY WORKWEAR GARMENTS USE THE CORRECT CARE LABELLING SUITED TO THEIR TYPE AND FABRICATION
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling
BISLEY WORKWEAR GARMENTS ACCURATELY LIST THE FABRIC FIBRE CONTENT
- **AS/NZS 4399:2017:** Sun Protective Clothing - Evaluation and Classification
THIS GARMENT HAS A SUN PROTECTION RATING OF UPF 50+ FOR ALL COLOURS
- **AS/NZS 1020:1995:** The Control of Undesirable Static Electricity
THIS GARMENT IS 100% COTTON WITH NO METAL ZIPS OR BUTTONS, THEREFORE IT MAY BE USED AS A STATIC CONTROL GARMENT

- **AS/NZS 1906.4:2010:** Hi Visibility Material For Safety Garments.
THIS GARMENT MEETS THE FLUORESCENT CAPABILITIES AND THE CHROMATICITY READING TO ENSURE THAT THE BRIGHT COLOURS ARE WITHIN THE REQUIRED COLOUR RANGE.
- **AS/NZS 4602.1:2011:** Hi Visibility Safety Garments. Garments For High Risk Application.
THIS GARMENT HAS A MINIMUM OF 0.2sqm OF HI VISIBILITY FABRIC ON THE FRONT AND BACK TO MEET DAY STANDARD.
- **AS/NZS 1020:1995:** The Control of Undesirable Static Electricity
THIS GARMENT IS 100% COTTON WITH NO METAL ZIPS OR BUTTONS, THEREFORE IT MAY BE USED AS A STATIC CONTROL GARMENT

- **AS 7471:2019:** Australian Rail Personal Protective Equipment Minimum Requirements.
THIS GARMENT MEETS THE MINIMUM REQUIREMENTS FOR PPE WHEN ACCESSING THE RAIL CORRIDOR. FLUORESCENT ORANGE AND RETRO-REFLECTIVE TAPE MEETS REQUIREMENTS OF AS/NZS 1906.4:2010 AND DESIGN TO AS/NZS 4602.1:2011

International Standards

- **ISO 3758:2012:** Standard Guide for Care Labelling Code Using Symbols for Care Instructions on Textile Products. *BISLEY WORKWEAR GARMENTS COMPLY WITH ISO STANDARDS FOR CARE LABEL SYMBOLS AND CONTENT DESCRIPTIONS*
- **ISO 14184-1:** Textiles - Determination of Formaldehyde - Part 1: Free and Hydrolyzed Formaldehyde (Water Extraction Method)
BISLEY WORKWEAR GARMENTS ARE FREE FROM FORMALDEHYDE

OVERALLS

MENS

Sizes REGULAR	77R	82R	87R	92R	97R	102R	107R	112R	117R
To fit chest size (cm)	87	92	97	102	107	112	117	122	127
To fit chest size (inches)	34	36	38	40	42	44	46	48	50
To fit waist size (cm)	77	82	87	92	97	102	107	112	117
To fit waist size (inches)	30	32	34	36	38	40	42	44	46
In-leg length (cm)	80	80	82	82	84	84	86	86	87
Imperial/NZ size	3R	4R	5R	6R	7R	8R	9R	10R	11R

Sizes STOUT	87S	92S	97S	102S	107S	112S	117S	122S	127S	132S
To fit chest size (cm)	97	102	107	112	117	122	127	132	137	142
To fit chest size (inches)	38	40	42	44	46	48	50	52	54	56
To fit waist size (cm)	87	92	97	102	107	112	117	122	127	132
To fit waist size (inches)	34	36	38	40	42	44	46	48	50	42
In-leg length (cm)	78	78	80	80	82	82	83	83	83	83
Imperial Size	3.25S	4.25S	5.25S	6.25S	7.25S	8.25S	9.25S	10.25S	11.25S	12.25S
NZ size	5S	6S	7S	8S	9S	10S	11S	12S	13S	14S