

PennGrade 1[®] Break-In Oil SAE 30



Product Description

PennGrade 1[®] Break-In Oil SAE 30 provides wear control for critical engine parts while allowing the engine components to seat, resulting in maximum engine performance and life. It is formulated with premium base stocks and a state-of-the-art additive system. Available in SAE 30.

PennGrade 1[®] Break-In Oil SAE 30 is suitable for use in BOTH diesel and gasoline fueled engines. This makes PennGrade 1[®] Break-In Oil SAE 30 the optimum choice for professional engine builders.

Typical Properties

SAE Viscosity Grade	Test Method	30
Viscosity @ 100 °C, cSt	ASTM D445	11.3
@ 40 °C, cSt	ASTM D445	93.3
Viscosity Index	ASTM D2270	107
Pour Point, °F (°C)	ASTM D97	-30 (-33)
Flash Point, COC, °F (°C)	ASTM D92	440 (226)
Sulfated Ash, Weight %	ASTM D874	0.95
API Gravity @ 60 °F	ASTM D1298A	27.8
Density, lbs/gal (g/L)	Calculated	7.398 (888.3)
Color	ASTM D1500	Green
TBN	ASTM D2896	7.2

D-A Part Number:

Drum – 55 Gal
Case – 12/1 Qt

71202
71206

