





LinkLocator Reporting Armed	32	"\L"	N/A	Yes	No	No	No	Yes	Yes	Yes	Yes	No
LinkLocator Reporting Disarmed	33	"\V"	N/A	Yes	No	No	No	Yes	Yes	Yes	Yes	No
List of Available Commands	34	"h"	<ul style="list-style-type: none"> <li>• "\h" – Help for commands beginning with</li> </ul>	Yes	Yes	Yes*	Yes*	Yes*	Yes*	Yes*	Yes*	No
Low Level	35	"x" (lowercase X)	<ul style="list-style-type: none"> <li>• "\l" – Level Test</li> </ul>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Next	36	"n"	<ul style="list-style-type: none"> <li>• "\f" – First Family Search First</li> </ul>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Pass-Thru Mode	37	" " (vertical bar)	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
RAM & Register States Dump	38	"\I"	N/A	No	No	Yes	No	No	No	No	No	No
RAM & Register States Dump (LinkHub-S)	39	"!"	N/A	No	Yes	No	No	No	No	No	No	No
Read EEPROM ASCII Data	40	"\r"	N/A	No	Yes	Yes	No	No	No	No	No	No
Read EEPROM Hex Data	41	"\R"	N/A	No	Yes	Yes	No	No	No	No	No	No
Relax Timing	42	"(" (left parenthesis)	N/A	Yes	No	No	Yes	Yes	Yes	Yes	Yes	No

Report Active Channel Mask	43	"\c" (backslash + low	• "\C" Active Channe l Mask • "\s" Channe l	No	Yes	Yes	No	No	No	No	No	No
Report EEPROM Read/Write Address	44	"\m" (backslash + low	N/A	No	Yes	Yes	No	No	No	No	No	No
Report Maximum Internal EEPROM Address	45	"\E"	N/A	No	Yes	Yes	No	No	No	No	No	No
Report Scan List	46	"*"	• "\$" – Arrival/ Depart ure Scannin g	No	No	Yes	Yes	Yes	Yes	Yes	Yes	No
Search Type	47	"t"	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Set EEPROM Read/Write Address	48	"\M"	N/A	No	Yes	Yes	Yes	No	Yes	Yes	Yes	No
Sniffer Mode	49	"\\" "\" (For Link OEM)	N/A	No	No	No	Yes*	No	No	No	No	Yes
Status of Bus & Bus Reset	50	"r"	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Turn Off Dynamic Pull-Up	51	". " (period)	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No
Write EEPROM ASCII Data	52	"\w" (backslash + low	N/A	No	Yes	Yes	No	No	No	No	No	No
Write EEPROM Hex Data	53	"\W" (backslash + up	N/A	No	Yes	Yes	No	No	No	No	No	No

19,200 Baud Serial Port Data Rate	54	"," (comma)	N/A	Yes	Yes	No	Yes	Yes	No	No	No	No
38,400 Baud Serial Port Data Rate	55	"`" (accent)	N/A	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
57,600 Baud Serial Port Data Rate	56	"^" (caret)	N/A	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	No
115,200 Baud Serial Port Data Rate	57	":" (colon)	N/A	No	Yes	No	Yes	No	No	No	No	No