2027 SERIES

Horizontal Hold Down Clamps | Product Overview

Features:

- Increased handle clearance reduces pinch points
- Common mounting hole pattern to Model 227
- Fixed handle pivot provides smooth action
- Over 1½ times the holding capacity Model 227
- BLK models feature a black, non-reflective finish

Applications:

- Checking fixtures
- Assembly & test
- Light machining
- Woodworking
- Closures

Also Available:

See page MC-ACC-1 for accessories

Accommodates M8 or ⁵/₁₆" spindle accessory

Covered under one or more U.S./International Patents







2027-UR

Flanged Base, U-Bar with DESTACO® Toggle Lock



Note: Clamps shown with included accessories.


1 This item is available upon request

Technical Information

				_	Accessories (Supplied)		
Model	Max. Holding Capacity	Clamp Bar Opening (+10°)	Handle Opening (+10°)	Weight	Spindle Assembly	Flanged Washers	
2027-U	3740 N [840 lbf]	68°	70°	0,61kg [1.34lb]	2007208-M	507107	
2027-U-LS-BLK(i)						507107-BLK	
2027-UR					2007208-M	507107	

i This item is available upon request

Holding Capacities



Model	Х	X1	X2	Y	‡HC1	‡HC2	‡EF(X1):AF	‡EF(X2):AF
U/UR	[1.02]	[1.75]	[3.30]	[2.54]	[840lbf.]	[480lbf.]	5:1	3:1
	25,8	44,5	83,8	64,5	3740N	2140N		

Dimensions shown "mm [inch]" \ddagger HC = Holding Capacity, EF = Exerting Force, AF = Applied Force Refer to See page MC-TEC-4 for additional information.





Horizontal Hold Down Clamps | Dimensions | -U/-UR

2027-**U** Flanged Base [0.33] 8,3 U-Bar [2.22] 56,4 [0.12] 3,0 DESTACO® TOGGLE LOCK **PLUS OPTION** M8 OR 5/16-18 [1.32] 33,6 [0.75] 19,1 [2.25] 0 [0.16] 4,2 [2.86] 72,7 [0.28] 7,0 RANGE OF [4.42] 112,3 **ADJUSTMENT** [2.86] 72,8 [1.21] 30,8 [1.03] 26,2 [1.81] 45,9 [1.56] 39,6 [0.11] 2,8 [0.14] R3,4 [9.88] 250,9



mm [INCH]