



### General Features

- Compact design for space restrictions; min. service area
- Inlet above element for extended element life & maintenance intervals
- Cast, corrosion resistant aluminum top with machined connections: - Integrated baffle design  
- 4 M12 taps for mounting brackets: 2" to 6"
- "T" style design minimizes piping requirements
- 1/4" differential gauge ports: 2" to 6"

### ST Series Specifications

- See-through bucket made from polycarbonate material
- Bucket has a high tensile strength for dimensional stability
- Temp ratings: - Complete assembly max: 220°F (104°C)  
- See-through bucket only max: 257°F (125°C)
- Increased holding capacity

### Technical Specifications

- Vacuum Rating: Gas tight seal
- Temp (continuous): min -15°F (-26°C) max 220°F (104°C)
- Filter change out differential: 15-20" H2O over initial Δ P
- Polyester: 99%+ removal efficiency standard to 5 micron
- Paper: 99%+ removal efficiency standard to 2 micron

### Options

- Swing bolts for heavy duty environments
- 1" to 1-1/2" housings have dimples for optional gauge ports & mounting bracket taps
- Epoxy coated housings
- Drain ports
- Spool piece extender on select models
- ISO flange connections: NW25, NW40 (select models)

FPT Inlet & Outlet	Assembly SCFM Rating	Assembly Part Number		Dimensions - inches				Suggested Service HT. E	Approx. Weight lbs.	Replacement Element Part No.		Element SCFM Rating
		Polyester	Paper	A	B	C	D			Polyester	Paper	
1"	40	ST-897-100C	ST-896-100C	13 3/8	11 15/16	7	10 3/8	9	11	897	896	115
1-1/4"	60	ST-897-125C	ST-896-125C	13 3/8	11 15/16	7	10 3/8	9	11	897	896	115
1-1/2"	80	ST-897-150C	ST-896-150C	13 3/8	11 15/16	7	10 3/8	9	10	897	896	115
2"	175	ST-851/1-200C	ST-850/1-200C	16 1/4	14 1/4	9	12 1/2	9	15	851/1	850/1	290
2-1/2"	210	ST-851/1-250C	ST-850/1-250C	16 1/4	14 1/4	9	12 1/2	9	14	851/1	850/1	290
3"	300	ST-235P-300C	ST-234P-300C	19 3/4	17	13 1/2	14	9	29	235P	234P	570
4"	520	ST-235P-400C	ST-234P-400C	19 3/4	17	13 1/2	14	9	25	235P	234P	570

Dimension tolerance ± 1/4"

### CT Series Specifications

- Carbon steel black enamel drop down bucket
- Swing bolts standard on 6" housings

FPT Inlet & Outlet	Assembly SCFM Rating	Assembly Part Number		Dimensions - inches				Suggested Service HT. E	Approx. Weight lbs.	Replacement Element Part No.		Element SCFM Rating
		Polyester	Paper	A	B	C	D			Polyester	Paper	
1"	40	CT-897-100C	CT-896-100C	13 3/8	11 13/16	7	10 3/8	9	12	897	896	115
1-1/4"	60	CT-897-125C	CT-896-125C	13 3/8	11 13/16	7	10 3/8	9	12	897	896	115
1-1/2"	80	CT-897-150C	CT-896-150C	13 3/8	11 13/16	7	10 3/8	9	11	897	896	115
2"	175	CT-851-200C	CT-850-200C	13	10 7/8	9	9	9	16	851	850	290
2-1/2"	210	CT-851-250C	CT-850-250C	13	10 7/8	9	9	9	15	851	850	290
3"	300	CT-235P-300C	CT-234P-300C	18 5/8	16 1/8	13 1/2	13	9	30	235P	234P	570
4"	520	CT-235P-400C	CT-234P-400C	18 5/8	16 1/8	13 1/2	13	9	26	235P	234P	570
6"	1100	CT-275P-600C	CT-274P-600C	18 1/4	14 1/2	19	9 7/8	10	45	275P	274P	1100

Note CT 2" & 2-1/2" models: Element seals on the base of the housing.

See Vacuum Filter Technical Data section for sizing guidelines.

Note: Model offerings and design parameters may change without notice. See [www.solbergmfg.com](http://www.solbergmfg.com) for most current offering.