

H28 TJ+

Exceptional productivity

- Telescopic jib provides
 6 m (19 ft 8 in) additional
 outreach which is extremely
 practical for accessing work
 areas and for getting around
 obstacles
- 4 simultaneous and proportional movements
- Double load capacity: 350 kg / 770 lbs (3 persons) or 230 kg / 500 lbs (2 persons)
- Tailswing of 72 cm for more compactness

Optimal rough terrain driving features

- 4 wheel drive
- Front oscillating axle
- Differential wheel lock
- > 52 cm ground clearance



Haulotte >>>

More than lifting

230 kg / 2x T

350 kg / 3x


	G	• • •	0	U
•				

TECHNICAL DATA	H28 TJ+	
Working height	27.5 m	
Platform height	25.5 m	
Horizontal outreach	22.6 m	
Lift capacity	230 - 350 kg	
f x G Platform size	1.8 x 0.8 m	
A Length - stowed	12.35 m	
① Length - storage	9.45 m	
B Width	2.49 m	
Width - with extended axles	N/A	
C Height - stowed	2.95 m	
Height - storage	2.95 m	
Vertical jib rotation	133° (+63°/-70°)	
Platform rotation	180° (+90°/-90°)	
Boom rotation angle	75 °	
Turntable rotation	360° continuous	
Tailswing	72 cm	
Wheelbase	3 m	
■ Ground clearance	52 cm	
Tilt	4 °	
Drive speed	0.5 - 5 km/h	
Gradeability	40 %	
Turning radius - outside	7.45 m	
Tires - foam-filled	385-45-28	
Engine	55 kW - 75 hp	
Weight	17300 kg	

	80 ft 70 ft 60 ft 50 ft 40 ft 30 ft 20 ft 10 ft 0 ft -10 ft
30,5 m	
27,4 m	
24,4 m	
21,3 m	
18,3 m	
15,2 m	
12,2 m	
9,1 m	
6,1 m	
3 m	
0 m	
	24.4 m 21.3 m 18.3 m 15.2 m 12.2 m 9.1 m 6.1 m 3 m 0 m -3 m

STANDARD EQUIPMENT

- 4 wheel drive, 2 wheel steer
- · Front oscillating axle increasing stability on uneven ground
- · Differential wheel lock increasing rough terrain capacity
- · Proportional controls enhancing comfort and safety
- 4 simultaneous movements for highest productivity
- Telescopic jib with octagonal cross section for additional versatility and optimal rigidity
- Dual load capacity: 230 kg (2 persons) / 350 kg (3 persons)
- · Sound and light alarm for tilt and load
- Electric pump system and emergency descent
- 12 V battery / electrical control system
- Swing out engine tray for ease of maintenance
- Safe to use in winds up to 45km/h / 28mph
- Hydrostatic transmission
- Low fuel level indicator (upper control box)
- Engine pre-heater with light indicator
- Hourmeter
- Tow hooks and lift hooks



OPTIONS AND ACCESSORIES

- On-board 3.3kW generator
- Cold weather kit
- Power to platform (Female plug in the basket 110V/220V)
- Alarm package (motion alarm and travel alarm)
- Travel alarm
- Rotating beacon
- 15W flashing light
- Air line to platform
- 55W platform working light
- Hydraulic oil cooler
- Hydraulic oil in tank and circuit for warm countries
- Biodegradable hydraulic oil
- Upper control box protection cover (transparent plastic and fixed place)
- 30 mA circuit-breaker
- Large platform 2.44 x 0.8m

