

Specifications

MODEL		GS™-3384 RT	
MEASUREMENTS		US	Metric
Working height maximum*		39 ft	12.06 m
A Platform height maximum		33 ft	10.06 m
B Platform height - stowed**		5 ft 1 in	1.55 m
C Platform length:			
outside, extended - single deck		13 ft .5 in	3.98 m
outside, extended - dual deck		17 ft 6.25 in	5.34 m
D Slide-out platform extension deck - front		5 ft	1.52 m
E Slide-out platform extension deck - rear		4 ft	1.22 m
F Platform width - outside		6 ft	1.83 m
G Height - stowed:			
folding guardrails		8 ft 9.5 in	2.68 m
rails lowered		6 ft 6.75 in	2.0 m
H Length - stowed:			
single deck		12 ft 11.25 in	3.94 m
dual deck		13 ft 5 in	3.98 m
with outriggers		16 ft	4.88 m
I Width:			
standard tires		7 ft	2.13 m
high flotation tires		7 ft 11 in	2.41 m
J Wheelbase		9 ft 4 in	2.84 m
K Ground clearance - center		13 in	.33 m

PRODUCTIVITY		
Maximum platform occupancy	7	7
Lift capacity	2,500 lbs	1,134 kg
Lift capacity - extension deck	500 lbs	227 kg
Drive speed - stowed	4.0 mph	6.4 km/h
Drive speed - raised	0.7 mph	1.1 km/h
Gradeability - stowed***	50%	
Maximum outrigger leveling:		
front to back	7°	
side to side	12°	
Turning radius - inside	10 ft 1.5 in	3.09 m
Turning radius - outside	19 ft 6 in	5.94 m
Raise/lower speed	45/29 sec	
Controls	proportional	
Drive	four wheel	
Tires - foam-filled rough terrain	10 x 31 in	25 x 79 cm

POWER		
Power source	Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW)	
	Deutz D2011L03i 3 cylinder diesel 49 hp (36 kW) air cooled	
Auxiliary Power unit	12 V DC	
Fuel tank capacity	30 gal	113.6 L
Hydraulic system capacity	30 gal	113.6 L

WEIGHT****		
	12,005 lbs	5,445 kg
with outriggers	13,680 lbs	6,205 kg

STANDARDS COMPLIANCE ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Based on RT tires. Deduct 2 in (5.8 cm) for turf and non-marking.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards.

