3394RT Diesel Scissor Lift



QUESTIONS TO ASK

- . What are the ground conditions in the work area?
- Is the site level, will you need auto level stabilisers?
- . What is the rated capacity needed for the job?
- Do you need an extension lead outlet in the platform?
- · Do you need an extension deck at both ends of the platform?

KEY SELLING POINTS

- · Smooth control, proportional drive, lift and lower
- Deutz F3M2011 diesel engine with increased HP output
- Fold down rails allows drive through a 203cm high door
- · Extension platform has fold down rails
- · Extension deck at both ends of the platform
- · Kick arm on lift cylinder provides cushioned lowering
- Puncture-proof lug pattern urethane filled non-marking tyres
- · Constant traction 4 wheel drive for 45 per cent gradeability
- · Oscillating front steer axle
- · Wide scissor stack provides rigidity and stability
- · Extended stabilisers prevent drive
- Auto level stabiliser feature allows adjust lateral stabiliser levelling from steer switch
- Multi axis 4 degree level sensor
- Plug in JLG analyser to indicate system functions for servicing and adjustment
- · Removable platform control box

APPLICATIONS

- · Facilities maintenance
- · Shopping centres and other outdoor areas
- Electricians
- Plumbers
- Wall panel installers
- · All maintenance and construction work
- · Aircraft maintenance, outdoor rated, large deck capacity
- · Tilt up panel building and factory fit outs

SPECIFICATIONS

Performance:	
Platform Height (max.)	10.06m
Working Height	12.06m
Lift Time	30 sec
Lower Time	30 sec
Platform Capacity Standard	907kg
Dimensions:	
Stowed Height - Rails Up	2.67m
Stowed Height - Rails Lowered	1.97m
Minimum Transport Length	3.86m
Overall Width	2.39m
Wheelbase	2.95m
Ground Clearance	0.3m
Platform Width	2.18m
Platform Length	3.81m
Standard Platform Extension - Side	e 1 1.22m
Standard Platform Extension - Side	2 1.22m
Stabiliser Levelling - Fore and Aft	Auto
Stabiliser Levelling - Side to Side	Auto/Manual
Platform Height Lowered	1.57m
Maximum Drive Height	10.06m
Power:	
Power Source	Diesel
Engine Make	Deutz
Engine Model	D2011 L03
Engine Power	37kW
DC Voltage	12V
DC Power	850CCA Amp h
Auxiliary Power	Manual
Drive Motors - Type	Piston
Hydraulic Pump - Type	Gear
Hydraulic Pump Drive Motor Type	Piston
Travel:	
Tyre Size	15.5 x 16.5
Tyre Type	Foam Filled/Non Marking
Inside Turn Radius	2.71m
Outside Turn Radius	5.93m
Drive Speed Elevated	0.6km/h
Gradeability	45%
Weights and Capabilities:	
Fuel Tank Capacity	113.56 Ltr
Hydraulic Tank Capacity	151.42 Ltr
Operating Weight	6,600kg
CHOOL CARE THE CONTRACT OF THE POPLET	METAL YORK THE TAX TO SEE THE SECOND SECOND