



Geometry

	XS	S	M	L	XL
Stack	536	558	579	606	628
Reach	363	366	375	382	393
TT Length (virtual)	507	526	547	568	588
ST length (actual)	415	455	492	537	574
Head Tube Length	125	147	164	191	214
Top Tube Slope	19	17	15	13	11
Head Angle	70.75	71.00	71.50	72.00	72.50
Seat Tube Angle	75.00	74.00	73.50	73.00	72.75
Chainstay Length	420	420	420	420	420
BB Drop	80	80	80	80	77
Fork Rake	53	53	45	45	45
Standover Height	693	728	759	798	831
Front Center	584	592	595	606	619
Wheelbase	991	999	1002	1013	1027
Fork Length	380	380	380	380	380

Technical Features

Construction	One-piece, UD (uni-directional) carbon monocoque frame and fork
Design	All-road geometry with modular Flex-Fit system
TT Slope	Sloping, 11-19 degrees (size-specific)
Seat Stays	Twin, individual stays
Tire Clearance	28-38mm (measured)
Seatpost	31.6mm, round, 0mm or 25mm offset, replaceable external clamp
Cabling	Full internal routing, electronic drivetrain only
Bottom Bracket	T47, internal, 85.5mm width
Drop Outs	142mm thru-axle, UDH (Universal Derailleur Hanger) compatible, 140/160 rotors
F. Derailleur	Braze-on, removable, includes 1x blanking panel
Standard Finish	Nude, waxed carbon - Parlee Paintlab custom paint available
Fork Specs	Full carbon, integrated crown race, hidden cabling, flat mount disc, 100mm thru-axle, 160/180 rotor compatible
Headset	Integrated IS52 upper and lower, stainless bearings
Flex-Fit Spacers	Included ENVE, FSA, and PRO short and tall top caps