

DATALOGGER[®] 7

FUSION JOINT DATA COLLECTION & ANALYSIS



STANDARD FEATURES

- ✓ Document fusion joint, operator and machine details including GPS locations
- ✓ Capture electrofusion, squeeze off techniques and pressure testing data
- ✓ 14+ hour battery capacity and a hot-swappable battery option
- ✓ IP68-rated rugged base tablet is waterproof, dust proof and shock proof
- ✓ Easy, simple-to-follow guided workflow
- ✓ Hard keys for easy navigation between applications
- ✓ Large, sunlight-readable 7" display with best-in-class outdoor visibility and clarity
- ✓ Automatic data backup to included SD card
- ✓ McElroy Optimized Cooling™ algorithm allows for more joints to be completed in less time



Capture the most important data from your fusion jobsite—no matter how long the workday. The DataLogger[®] 7 delivers increased battery life, automatic data backup, an updated Android operating system and more in a new, IP68-rated and MIL-STD-810 tested, rugged touchscreen tablet.

The DataLogger software helps to ensure that every joint was fused with the correct pressure and times according to supported standards by recording key parameters of the fusion process. Document heat soak times, heating pressure, open/close times, fusion time, fusion pressure, cool time along with jobsite details and operator information. A real-time graph gives immediate visual feedback regarding the integrity of each fusion joint. Joint records can be securely stored and analyzed online in the McElroy Vault™ - allowing quick and easy sorting, tagging and sharing of joint records by machine, joint, operator, device or job.

SEE SECOND PAGE FOR DETAILED SPECIFICATIONS

DATALOGGER[®] 7

FUSION JOINT DATA COLLECTION & ANALYSIS

SPECIFICATIONS

MODELS		SCREEN		PERFORMANCE (CONTINUED)	
DLP0857716	DataLogger 7 - English, Spanish, and Russian	Active Viewing Area	7" (177.8 mm)	RAM	6 GB LPDDR4x
WEIGHTS		Resolution	WXGA (1280 x 800)	Protection	IP68 waterproof, dustproof and shockproof (multiple drops from 4' (1.2 - 1.5 m) onto concrete), designed to meet MIL-STD-810G test procedures
Machine	1.5 lbs. (0.7 Kg)	Touchscreen	Dragontrail™ High Ion-Exchange (HIE™)	Storage Capacity	64 GB or 128 GB flash storage options
MACHINE DIMENSIONS		PERFORMANCE		Storage Temperature	-22 F to 158 F (-30 C to 70 C)
Length	8.5" (215.4mm)	Battery	Removable Li-ion battery with 43.2 Whr and Internal 21.6 Whr battery providing hot-swap capability	CONNECTIVITY	
Width	5.4" (137.2mm)	Expandable Storage	User-accessible MicroSDXC card slot	Bluetooth	Long-range Bluetooth® Smart Ready wireless technology, v5.0 + EDR, Class 1.5, BLE support
Height	1.4" (34.5mm)	Operating System	Android 9	Cellular Data	4G LTE multi-carrier capable
SUPPORTED STANDARDS		Operating Temperature	-4 F to 122 F (-20 C to 50 C)	Wi-Fi	802.11 a/b/g/n/ac, 2.4 GHz and 5 GHz, 2x2 MIMO
Data Logging	ASTM F3124	Processor	Qualcomm® Snapdragon™ Octa-core Kryo™ 260	CAMERA	
Fusion	ASTM F2620, ISO 21307:2011-05, GIS/PL2-3-07, Profuse, DS /INF 70-2 PE:HD:1992-05, WIS 4-32-08:2002-04, DVS 2207-1 PE:HD:2005-09, DVS 2207-11 PP:2008-08, DS/INF 70-2 PP:1992-05	INCLUDES		Front Camera	2 MP
				Rear Camera	16 MP with LED illumination