

GOLDSTRIKET REAR FENDER TIP

1 1

Parts Included:

Fender tip Primer

INSTALLATION INSTRUCTIONS:

- 1. Park on a level surface and shut off the motorcycle. Ensure the engine has time to cool before installation.
- 2. Clean the rear fender with soap and hot water to remove all dirt and debris.
- 3. ATTENTION: Thoroughly clean the mounting surface with denatured alcohol to remove all wax, oil, and residue. NOTE: New motorcycles are delivered from the factory covered in protective oil. Remove it before installing this product. NOTE: Do not install if the temperature is below 50° F. The adhesive will not cure properly.
- 4. Test fit the fender tip to familiarize yourself with its natural location. The fender tip is designed to fit over the peak of the chamfer above the edge of the fender, not at the fender edge. (Fig.2)
- 5. Place masking tape around the edge of the fender tip so you can see where to apply the primer. (Fig.1)
- 6. Apply the primer according to the instruction on its container. (Fig.1)
- 7. Remove the red adhesive backing and install fender tip. Press the fender tip firmly onto the surface for 60 seconds. The adhesive cures within 24 hours.Fi



WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure. Ciro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly

- installed and maintained.
- Ciro will not be liable for any
- consequential and incidental
- damages, including labor, or non-Ciro products.
- Please visit our website
- Ciro3d.com for our complete
- warranty policy.

G0078450, REV. -