



GOLDSTRIKE LICENSE PLATE FRAME

Parts Included:

- 1 Frame
- 1 Backing Plate
- 1 1/4-20 Phillips Screw
- 2 1/4-20 Hex Head Bolts
- 2 1/4-20 Lock Nuts
- 2 1/4 Washers

Recommended tools:

- #2 Phillips screw driver
- 1/4" Drive ratchet wrench
- 7/16" Socket

INSTALLATION INSTRUCTIONS:

1. Park on a level surface and shut off the motorcycle. Ensure the engine has time to cool before installation.
2. Remove the license plate and hardware from the motorcycle. Pic.1
3. Install the 1/4-20 hex bolts into the Goldstrike Backing Plate and place it on the fender. Pic.2
4. On the back side of the fender. Install the 1/4 washers and 1/4-20 hex nuts on the bolts and tighten them with a 7/16 socket and wrench.
ATTENTION: Make sure the part is centered and level with the motorcycle before tightening the fasteners.
ATTENTION: Do not over tighten the nuts and bolts.
5. Bend your license plate into a slight curve and lay it onto the Goldstrike backing plate. Pic.3
6. Hook the top of the Frame onto the Backing Plate. Push it down and install the 1/4-20 Phillips head screw Pic.4
ATTENTION: Do not over tighten the screw.



Pic.1



Pic.2



Pic.3



Pic.4

WARNING:

This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION:

This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION:

This indication alerts you to the fact that if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation.

NOTE:

Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure.

Ciro will have no obligation if the customer cannot show proof of purchase.

Warranty will not be granted unless the part is properly installed and maintained.

Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products.

Please visit our website Ciro3d.com for our complete warranty policy.