



KERRADECO. DECORATIVE WALLS

TECHNICAL DATA SHEET

Profile Type	Kerradeco
Material	PVC-UE
Total length	1350 mm / 2700 mm / 3000 mm
Total width	295 mm
Weight	1,6 kg/m
Thickness	9 mm
Packing	1350 mm - 8 pc./cardboard 2700 mm - 4 pc./cardboard 3000 mm - 4 pc./cardboard
Coverage area/pack	1350 mm - 3,186 m ² 2700 mm - 3,186 m ² 3000 mm - 3,540 m ²
Storage	The product should be stored in covered rooms, out of the reach of heating devices and direct sunlight. In conditions that protect the panels against contamination, deformation and mechanical damage.
Tools	You can use a hand saw, jigsaw or table saw for cutting.
Joint	Tongue-and-groove joint
Installation temperature	Before installation, the panels should be left in the room where they will be installed in order to equalize their temperature with the ambient temperature.
Important installation information	<ul style="list-style-type: none">- arrange the panels according to the numbering on the back of the panel- the product can be installed in humid rooms (kitchen, bathroom), provided that it is sealed with silicone.- do not install in places exposed to high temperatures (above 60 ° C)- assembly on a frame - distance between battens 40 cm,- glue mounting - smooth, non-flaking substrate, glue based on a hybrid polymer.
Maintenance	Occasionally clean it with water, a mild detergent and a cloth. Do not leave liquid stains to dry. Vigorous scrubbing and the use of harsh cleansers may damage the surface of the panel or



	discolor the panel. Do not clean with sharp and coarse cloths, sponges and brushes. Do not use solvents, acids or liquids based on these ingredients for cleaning. Do not leave cleaning agents on the surface, rinse thoroughly with water after cleaning; leaving the cleaning agents on the surface may cause discoloration.
Environmental characteristics	100% recyclable

Essential characteristics	Performance properties	Assessment methods
Impact resistance	Not less than 20J (23,20)	PN-EN 13245-2:2009/AC:2010
Release of hazardous substances	A+	
Reaction to fire	B-s3;d0	
Fastening strength	See: Assembly instruction	



QUICK TO INSTALL



LOW WEIGHT



IMPROVES SOUND INSULATION



EASY TO KEEP CLEAN



SUITABLE FOR RECYCLING



RESISTANCE TO MECHANICAL DAMAGE



10-YEAR WARRANTY



RESISTANCE TO UV RADIATION



SAFE IN CONTACT WITH FOOD



WATERPROOF

