

## **Keyboard Features:**

PC Smart Card Reader **Smart Card application** required **FiPS Publication** 201 compliant Connects via USB cable LEDs indicate card status & power PC Smart Card Standard (PC/SC) compliant Chip Card Interface Device (CCID) compatible **Card Terminal Application** Interface (CT/API) applications Home Banking Computer Interface (HBCI) applications Windows® XP® (SP2+), Vista®, 7, 8 & 10 compatible

## **Technical Specifications:**

Dimensions: 2.6" (W) x 2.6" (D) x 0.5" (H) Card Reader Interface: ISO 7816-1, 2. 3. T0, T1=1 protocol Smart card connector: 8 pin, Friction Technology Durability: Up to 200,000 cycles

## SMK-Link® TAA Compliant USB Smart Card Reader

The SMK-Link® VP3805-TAA is a TAA-Compliant USB PC Smart Card Reader designed for GSA Schedule sales to government and military agencies, their VARs and vendors, and other organizations requiring components meeting U.S. Trade Agreements Act manufacturing specifications.

Connecting via USB cable, the VP3805-TAA Smart Card Reader is *PC Smart Card standard* (*PC/SC*) compliant and *CCID-compatible*, supporting *Card Terminal* (*CT/API*) and Home Banking (*HBCI*) applications. (Windows® XP\* (SP2+), Vista, 7.8 & 10 compatible.)



Use PC Smart Cards via USB
TAA Compliant



© 2015 SMK-Link Electronics, Inc. SMK-Link and the SMK-Link Logo are trademarks or registered trademarks of SMK-Link Electronics, Inc. Microsoft, Windows, XP and Vista are registered trademarks of Microsoft Corporation. Apple and OS X are registered trademarks of Apple Inc. All other trademarks and registered trademarks are properties of their respective owners.



3601 Calle Tecate, Suite B Camarillo, CA, 93012 888-696-3500 www.smklink.com