

AutoSeal® FD 1402

LOW-VOLUME PRESSURE SEALER

Standard Features:

- Compact Desktop Design: The user-friendly design provides easy installation and operation
- Drop-In Top Feed System: Produces dependable feeding of forms with no paper fanning required
- 14" Form Length Capability: Flexibility to process forms up to 14" in length
- Speed: Up to 73 forms per minute
- Fold Types: Folds Z, C, Uneven Z, Uneven C, Half and custom folds
- LED Indicators: Notify an operator when the power is on, a cover is open, the paper runs out or a fault occurs
- Hopper Capacity: Up to 160 forms, 20#
- Easy-Adjust Pre-Marked Fold Plates: Makes changing fold type or form size quick and easy
- Six-Digit resettable Counter: Provides maximum audit control

Options:

- Locking Cabinet: Fully enclosed for storage
- 402 Series Jogger: Reduces static electricity from forms and aligns them for proper feeding



Economical Pressure Seal Solution

The FD 1402 AutoSeal® offers a user-friendly low-volume solution for processing onepiece pressure sensitive mailers. With a speed of up to 73 forms per minute and the ability to process forms up to 14" in length, the FD 1402 enables operators to complete daily processing jobs with ease.

Standard features include redesigned fold plates that are clearly marked and easier to adjust, a control panel with six-digit resettable counter, and drop-in top feed system, all in a compact and sleek desktop design. Fold plates are pre-marked for standard folds for 11" and 14" form sizes, and can be easily adjusted for custom folds.

Built in the USA with proven Formax technology, the FD 1402 is an economical solution with the quality and reliability you have come to expect from Formax.

WWW.WHITAKERBROTHERS.COM 3 TAFT COURT ROCKVILLE. MD 20850 800-243-9226

Flexible

The FD 1402 handles a variety of pressure seal forms up to 8 1/2" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

Dependable & Powerful


The FD 1402 is built with proven Formax technology. Heavy-duty steel construction offers the dependability and power expected of a larger unit in a smaller package. With a processing speed of up to 73 forms per minute, operators can complete daily jobs in no time.



User-friendly Control Panel

Pressure Seal Solution

The AutoSeal® FD 1402, combined with a laser printer and pressure seal forms, creates a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

Easy to Operate

Right out of the box, the FD 1402 is easy to install and operate within minutes. Simply set your folds according to the clearly marked settings on the fold plates, load your forms using the drop-in feed system, press start and you're on your way. A conveniently located LED indicator lights up notifying the operator when a cover is open, the paper is out, or a fault occurs.

Factory Direct Warranty Support

The FD 1402 comes standard with a 90-day factory direct warranty** that includes phone support and depot service.

The following optional on-site services are also available:

- On-site installation and training only (one visit), by our local provider.
- Service Contract providing preventative maintenance and on-site support after the 90-day warranty. (On-site installation and training not included with service contract but available separately.)

Specifications:

Hopper Capacity:	Up to 160 Sheets 20#
Fixed Speed:	Up to 73 sheets per minute - based on 11" "Z" fold
Paper Size*:	Up to 8.5" W x 14" L
Usage:	Low-volume
Power:	120 Volts AC 50/60Hz
Dimensions:	24" L x 17" W x 13" H
Weight:	81 lbs
Certifications:	UL, CE and CUL Approved
Made in the USA	

^{*} Will not process 14" uneven "C" forms, or uneven "Z" forms with an address panel less than 3 inches long.

U.S. Patents: 5,772,841 5,865,925 5,968,308 6,264,592 Other Patents Pending



Redesigned fold plates -Clearly marked and easier to adjust



402 Series Jogger - an option which reduces static electricity from forms and aligns them for proper feeding

^{** 90-}day factory warranty begins at time of shipment to customer.